Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **A473**
Product name **ENGINE CLEANER 400 ml AMBRO-SOL**

UFI : **UQP1-Q0EK-1006-TNG4**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Aerosol product for external cleaning of engines.**

Identified Uses	Industrial	Professional	Consumer
Consumer	-	-	✓
Industrial Use	✓	-	-
Professional Use	-	✓	-

1.3. Details of the supplier of the safety data sheet

Name **AMBRO-SOL S.R.L. SB**
Full address **Via per Pavone del Mella, 21 - 23**
District and Country **25020 Cigole (BS)**
Italia
Tel. +39 030 9959674

e-mail address of the competent person responsible for the Safety Data Sheet **regulatory@ambro-sol.com**

Supplier: **Importer: Ambro-Sol UK Ltd, Express Park, Bridgwater, Somerset, TA6 4RR, UK, info@ambro-sol.co.uk, phone number / emergency number +44 1278 552999**

1.4. Emergency telephone number

For urgent inquiries refer to

IT - Centro Antiveleni di Milano - Ospedale Niguarda: Tel. 02 66101029 (Italy)
AT - Vergiftungsinformationszentrale (VIZ): Tel. +43 01 406 4343 (Austria)
BE - Belgisch Antigifcentrum: Tel. 070 245245 (Belgium)
BG - НАЦИОНАЛЕН ЦЕНТЪР ПО ТОКСИКОЛОГИЯ: Tel. +359 2 9154 233 (Bulgaria)
HR - Centar za kontrolu otrovanja: Tel. +385 1 2348342 (Croatia)
CY - Τμήμα Επιθεώρησης Εργασίας (TEE): Tel. 1401 (Cyprus)
CZ - Toxikologické informační středisko (TIS): Tel. +420 224 919 293 / +420 224 915 402 (Czech Republic)
DK - Giftlinjen: Ring 82 12 12 12 (Denmark)
EE - Mürgistusteabekeskus: Tel. 16662 (Estonia)
FI - Myrkytystietokeskus: Tel. 0800 147 111 / 09 471 977 (Finland)
FR - ORFILA (INRS): Tél. +33 (0) 1 45 42 59 59 (France)
DE - Giftnotruf der Charité Universitätsmedizin Berlin: Tel. +49 030 19240 (Germany)
GR - Κέντρο Δηλητηριάσεων: Τηλ. 210 7793777 (Greece)
HU - Egészségügyi Toxikológiai Tájékoztató Szolgálat (ETTSZ): Tel. +36 80 20 1199 (Hungary)
IS - Eitrunarmiðstöð: Tel. 543 2222 (Iceland)
IE - National Poisons Information Centre (NPIC): Tel. 01 8092566 / 01 8379964 (Republic of Ireland)
LV - Latvian Poisons Information Centre: Tel. +371 67042473 (Latvia)
LT - Apsinuodijimų Informacijos biuras: Tel. 8-5 236 2052 (Lithuania)
LU - Giftinformationszentrum: Tel. +352 8002 5500 (Luxembourg)
NL - Nationaal Vergiftigingen Informatie Centrum (NVIC): Tel. 030 274 88 88 (Netherlands)
NO - Giftinformasjonen: Tel. 22 9 13 00 (Norway)
PL - Pomorskie Centrum Toksykologii: Tel. +58 682 04 04 (Poland)
PT - Centro de Informação Antivenenos (CIAV): Tel. 800 250 250 (Portugal)
RO - Biroul RSI Si Informare Toxicologica: Tel. 021 318 36 06 (Romania)
SK - Národné Toxikologické informačné centrum (NTIC): Tel. 02 5477 4166

(Slovakia)
SI - Center za klinično toksikologijo in farmakologijo: Tel. 112 (Slovenia)
ES - Servicio de Información Toxicológica (SIT) España: Tel.+34 91 562 04 20 (Spain)
SE - Giftinformationscentralen: Tel. 112 (Sweden)
CH - Schweizerisches Toxikologisches Informationszentrum (STIZ): Tel. +41 145 (Switzerland)
GB - National Poisons Information Service (NPIS) Tel. 0344 892 0111 (United Kingdom)
Members of the Public: NHS 111 (England), NHS 24 (Scotland) or NHS Direct (Wales)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.
Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1	H222	Extremely flammable aerosol.
	H229	Pressurised container: may burst if heated.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.
Hazardous to the aquatic environment, chronic toxicity, category 2	H411	Toxic to aquatic life with long lasting effects.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal word: Danger

Hazard statements:

H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251	Do not pierce or burn, even after use.
P410+P412	Protect from sunlight. Do no expose to temperatures exceeding 50°C / 122°F.
P501	Dispose of contents/container in accordance with local regulations.
P102	Keep out of reach of children.
P101	If medical advice is needed, have product container or label at hand.
P211	Do not spray on an open flame or other ignition source.

Contains: Hydrocarbons, C6, isoalkanes, <5% n-hexane
Methyl acetate

SECTION 2. Hazards identification ... / >>

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification		x = Conc. %	Classification (EC) 1272/2008 (CLP)
Hydrocarbons, C6, isoalkanes, <5% n-hexane			
INDEX	*649-328-00-1*	58 ≤ x < 59,5	**Flam. Liq. 2 H225, Asp. Tox. 1 H304, Skin Irrit. 2 H315, STOT SE 3 H336, Aquatic Chronic 2 H411, Classification note according to Annex VI to the CLP Regulation: P**
EC	*931-254-9*		
CAS	*64742-49-0*		
REACH Reg.	*012119484651-34-XXXX*		
Propane			
INDEX	*601-003-00-5*	19 ≤ x < 20,5	**Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: U**
EC	*200-827-9*		
CAS	*74-98-6*		
REACH Reg.	*01-2119486944-21-0046*		
Butane			
INDEX	*601-004-00-0*	9 ≤ x < 10,5	**Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: C, U**
EC	*203-448-7*		
CAS	*106-97-8*		
REACH Reg.	*01-2119474691-32-XXXX*		
Methyl acetate			
INDEX	*607-021-00-X*	5 ≤ x < 6,5	**Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066**
EC	*201-185-2*		
CAS	*79-20-9*		
REACH Reg.	*01-2119459211-47-XXXX*		
Carbon Dioxide			
INDEX		3,7 ≤ x < 3,9	**Press. Gas (Comp.) H280**
EC	*204-696-9*		
CAS	*124-38-9*		
Isobutane			
INDEX	*601-004-00-0*	1,5 ≤ x < 1,6	**Flam. Gas 1A H220, Press. Gas H280**
EC	*200-857-2*		
CAS	*75-28-5*		
REACH Reg.	*01-2119485395-27-XXXX*		
Methanol			
INDEX	*603-001-00-X*	1,3 ≤ x < 1,4	**Flam. Liq. 2 H225, Acute Tox. 3 H301, Acute Tox. 3 H311, Acute Tox. 3 H331, STOT SE 1 H370**
EC	*200-659-6*		**STOT SE 2 H371: ≥ 3% - < 10%**
CAS	*67-56-1*		**ATE Oral: 100 mg/kg, ATE Dermal: 300 mg/kg, ATE Inhalation mists/powders: 0,501 mg/l**
REACH Reg.	*01-2119433307-44-XXXX*		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.
Percentage of propellants: 34,62 %

Hydrocarbons, C6, isoalkanes, <5% n-hexane
Hydrocarbons, C6, isoalkanes, <5% n-hexane: a complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C4 through C11 and boiling in the range of approximately minus 20Â ° C to 190Â ° C (-4Â ° F to 374Â ° F).

Isobutane
Note Isobutane: This product contains < 0.1 % w/w 1,3 butadiene (EINECS 203-450-8). This product should be considered as non-carcinogenic and non-mutagenic

SECTION 4. First aid measures

4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.
In case of more severe symptoms, ask for immediate medical aid.
EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.
SKIN: Take off contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice. Avoid further contact with contaminated clothing.
INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.
INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

Call a POISON CENTER or doctor/physician if you feel unwell.

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT
The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.
UNSUITABLE EXTINGUISHING EQUIPMENT
None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE
If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION
Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.
SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS
Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably

SECTION 6. Accidental release measures ... / >>

equipped. Wear protective gloves / protective clothing / eye protection / face protection.

6.2. Environmental precautions

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

7.2. Conditions for safe storage, including any incompatibilities

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.28 от 2 Април 2024г.)
CZE	Česká Republika	NAŘÍZENÍ VLÁDY ze dne 18. října 2023, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	WirkungDosisNOAELMAK-und BAT-Werte-Liste 2024 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe
DNK	Danmark	BEK nr 291 af 19/03/2024 (Historisk) Bekendtgørelse om grænseværdier for stoffer og materialer (kemiske agenser) i arbejdsmiljøet
ESP	España	Límites de exposición profesional para agentes químicos en España 2024
EST	Eesti	Ohtlike kemikaalide ja neid sisaldavate materjalide kasutamise töötervishoiu ja tööohutuse nõuded ning töökeskkonna keemiliste ohutegurite piirnormid 2024
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en FranceDécret n° 2021-1849 du 28 décembre 2021
FIN	Suomi	HTP-VÄRDEN 2020. Koncentrationer som befunnits skadliga. SOCIAL - OCH HÄLSOVÅRDSMINISTERIETS PUBLIKATIONER 2020:25
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ ''σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιγόνους παράγοντες κατά την εργασία''»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
LTU	Lietuva	Jsakymas dėl lietuvos higienos normos hn 23:2011 „cheminių medžiagų profesinio poveikio ribiniai dydžiai. Matavimo ir poveikio vertinimo bendrieji reikalavimai“ patvirtinimo
LVA	Latvija	Grozījumi Ministru kabineta 2007. gada 15. maija noteikumos Nr. 325 "Darba aizsardzības prasības saskarē ar ķīmiskajām vielām darba vietās" Oficiālās publikācijas Nr.: 2024/65.2
NOR	Norge	Forskrift om endring i forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og grenseverdier), 21. 10. april 2024 kl. 13.55
NLD	Nederland	Regeling van de Minister van Sociale Zaken en Werkgelegenheid van 13 mei2024, nr.

SECTION 8. Exposure controls/personal protection ... / >>

		2024-0000092805, tot wijziging van deArbeidsomstandighedenregeling in verband met de implementatie vanRichtlijn 2022/431
PRT	Portugal	Decreto-Lei n.º 102/2024, de 4 de dezembro. Sumário: Transpõe para a ordem jurídica interna a Diretiva (UE) 2022/431, relativa à proteção dos trabalhadores contra riscos ligados à exposição a agentes cancerígenos ou mutagénicos e procede à quarta alteração
POL	Polska	ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 24 czerwca 2024 r. zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
ROU	România	HOTĂRÂRE nr. 179 din 28 februarie 2024 pentru modificarea şi completarea Hotărârii Guvernului nr. 1.093/2006 privind stabilirea cerinţelor minime de securitate şi sănătate pentru protecţia lucrătorilor împotriva riscurilor legate de expunerea la agenţi ca
SWE	Sverige	Arbetsmiljöverkets föreskrifter och allmänna råd (AFS 2023:14) om gränsvärden för luftvägsexponering i arbetsmiljön
SVK	Slovensko	121_2024 Z. z. Nariadenie vlády o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénnym, mutagénnym alebo reprodukčne toxickým faktorom pri práci
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti rakotvornim, mutagenim ali reprotoksičnim snovem pri delu. Ljubljana, četrtek 4. 4. 2024
TUR	Türkiye	Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733; 20.10.2023 / 32345.
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	ACGIH	ACGIH 2025

Butane

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	1900				
AGW	DEU	2400	1000	9600	4000	
MAK	DEU	2400	1000	9600	4000	
TLV	DNK	1200	500	2400	1000	
VLA	ESP		1000			Gases
TLV	EST	1500	800			
VLEP	FRA	1900	800			
HTP	FIN	1900	800	2400	1000	
TLV	GRC	2350	1000			
AK	HUN	2350		9400		
RV	LVA	300				
TLV	NOR	600	250			
TGG	NLD	1430				
NDS/NDSCh	POL	1900		3000		
NPEL	SVK	2400	1000			
MV	SVN	2400	1000	9600	4000	
WEL	GBR	1450	600	1810	750	
WEL	GBR		4			RESP
ACGIH					1000	

SECTION 8. Exposure controls/personal protection ... / >>

Carbon Dioxide

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	9000	5000			
TLV	CZE	9000	4921	45000	24603	
AGW	DEU	9100	5000	18200	10000	
MAK	DEU	9100	5000	18200	10000	
TLV	DNK	9000	5000	18000	1000	E
VLA	ESP	9150	5000			
TLV	EST	9000	5000			
VLEP	FRA	9000	5000			
HTP	FIN	9100	5000			
TLV	GRC	9000	5000	54000	5000	
AK	HUN	9000	5000			
VLEP	ITA	9000	5000			
RD	LTU	9000	5000			
RV	LVA	9000	5000			
TLV	NOR	9000	5000			
TGG	NLD	9000				
VLE	PRT	9000	5000			
NDS/NDSCh	POL	9000		27000		
TLV	ROU	9000	5000			
NGV/KGV	SWE	9000	5000	18000 (C)	10000 (C)	
NPEL	SVK	9000	5000			
MV	SVN	9000	5000	18000	10000	
ESD	TUR	9000	5000			
WEL	GBR	9150	5000	27400	15000	
OEL	EU	9000	5000			
ACGIH		9000	5000	54000	30000	

Propane

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	1800				
AGW	DEU	1800	1000	7200	4000	
MAK	DEU	1800	1000	7200	4000	
TLV	DNK	1800	1000	3200	2000	
VLA	ESP		1000			
TLV	EST	1800	1000			
HTP	FIN	1500	800	2000	1100	
TLV	GRC	1800	1000			
RV	LVA	1800	1000			
TLV	NOR	900	500			
NDS/NDSCh	POL	1800				
TLV	ROU	1400	778	1800	1000	
MV	SVN	1800	1000	7200	4000	
ESD	TUR	1800	1000			

SECTION 8. Exposure controls/personal protection ... / >>

Methanol

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
TLV	BGR	260	200			SKIN	
TLV	CZE	250	188	1000	751	SKIN	
AGW	DEU	130	100	260	200	SKIN	
MAK	DEU	130	100	260	200	SKIN	
TLV	DNK	260	200	520	400	SKIN	E
VLA	ESP	266	200			SKIN	
TLV	EST	250	200	350	250	SKIN	
VLEP	FRA	260	200			SKIN	
HTP	FIN	270	200	330	250	SKIN	
TLV	GRC	260	200	325	250		
AK	HUN	260	200			SKIN	
VLEP	ITA	260	200			SKIN	
RD	LTU	260	200			SKIN	
RV	LVA	260	200			SKIN	
TLV	NOR	130	100			SKIN	
TGG	NLD	133				SKIN	
VLE	PRT	260	200			SKIN	
NDS/NDSCh	POL	100		300		SKIN	
TLV	ROU	260	200			SKIN	
NGV/KGV	SWE	250	200	350 (C)	250 (C)	SKIN	
NPEL	SVK	260	200			SKIN	
MV	SVN	260	200	1040	800	SKIN	
ESD	TUR	260	200			SKIN	
WEL	GBR	266	200	333	250	SKIN	
OEL	EU	260	200				
ACGIH		262	200	328	250	SKIN	

Predicted no-effect concentration - PNEC

Normal value in fresh water	20,8	mg/l
Normal value in marine water	2,08	mg/l
Normal value for fresh water sediment	77	mg/kg/d
Normal value for marine water sediment	7,7	mg/kg/d
Normal value for water, intermittent release	1,54	g/l
Normal value of STP microorganisms	100	mg/l
Normal value for the terrestrial compartment	100	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		8 mg/kg bw/d		8 mg/kg bw/d				
Inhalation	50 mg/m3	50 mg/m3	50 mg/m3	50 mg/m3	260 mg/m3	260 mg/m3	260 mg/m3	260 mg/m3
Skin		8 mg/kg bw/d		8 mg/kg bw/d		40 mg/kg bw/d		40 mg/kg bw/d

SECTION 8. Exposure controls/personal protection ... / >>

Methyl acetate

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	CZE	600	195	800	260	
AGW	DEU	620	200	1240	400	
MAK	DEU	310	100	1240	400	
TLV	DNK	455	150	910	300	
VLA	ESP	616	200	770	250	
TLV	EST	450	150	900	300	
VLEP	FRA	610	200	760	250	SKIN
HTP	FIN	610	200	770	250	
TLV	GRC	610	200	760	250	
AK	HUN	310	200	1240	400	SKIN
RD	LTU	450	150	900	300	
RV	LVA	100				
TLV	NOR	305	100			
TGG	NLD	100				
NDS/NDSCh	POL	250		600		
TLV	ROU	200	63	600	188	
NGV/KGV	SWE	450	150	900 (C)	300 (C)	
NPEL	SVK	310	100	770	250	
MV	SVN	620	200	1240	400	
ESD	TUR	610	200			
WEL	GBR	616	200	770	250	
ACGIH		606	200	757	250	

Predicted no-effect concentration - PNEC

Normal value in fresh water	120	µg/l
Normal value in marine water	12	µg/l

Health - Derived no-effect level - DNEL / DMEL

	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		NPI		44 mg/kg bw/d				
Inhalation	VND	VND	152 mg/m3		VND	VND	305 mg/m3	610 mg/m3
Skin			NPI	44 mg/kg bw/d	NPI	VND	NPI	88 mg/kg bw/d

Hydrocarbons, C6, isoalkanes, <5% n-hexane

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
NDS/NDSCh	POL	500		1500		

Health - Derived no-effect level - DNEL / DMEL

	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				1301 mg/kg bw/d				
Inhalation				1137 mg/m3				5306 mg/m3
Skin				1377 mg/kg bw/d				13964 mg/kg bw/d

Isobutane

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
ACGIH			800			

Legend:
(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.
VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low

SECTION 8. Exposure controls/personal protection ... / >>

hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.
When choosing personal protective equipment, ask your chemical substance supplier for advice.
Personal protective equipment must be CE marked, showing that it complies with applicable standards.
Provide an emergency shower with face and eye wash station.
HAND PROTECTION
None required.
SKIN PROTECTION
Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.
EYE PROTECTION
Wear airtight protective goggles (see standard EN ISO 16321).
RESPIRATORY PROTECTION
Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).
ENVIRONMENTAL EXPOSURE CONTROLS
The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.
Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	aerosol	
Colour	colourless	
Odour	characteristic of solvent	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	flammable gas	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	< 0 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	5-7	
Kinematic viscosity	not available	
Solubility	insoluble in water	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	0,65	
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

VOC (Directive 2010/75/EU)	95,50 %	-	623,48	g/litre
VOC (volatile carbon)	66,08 %	-	431,42	g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

Avoid overheating.

10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.
It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Methanol
WORKERS: inhalation; contact with the skin.
POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Methanol
The minimum lethal dose for humans by ingestion is considered to be in the range from 300 to 1000 mg/kg. Ingestion of 4-10 ml of the substance may cause permanent blindness in adult humans (IPCS).

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation - mists / powders) of the mixture:	> 5 mg/l
ATE (Oral) of the mixture:	>2000 mg/kg
ATE (Dermal) of the mixture:	>2000 mg/kg

Hydrocarbons, C6, isoalkanes, <5% n-hexane

LD50 (Dermal):	> 2000 mg/kg bw rabbit
LD50 (Oral):	> 2000 mg/kg bw rat
LC50 (Inhalation vapours):	> 25 mg/l/4h air (rat)

SECTION 11. Toxicological information ... / >>

Propane
LC50 (Inhalation mists/powders): 800000 ppm 15 min

Butane
LC50 (Inhalation mists/powders): > 1442,738 mg/l/15min rat

Methyl acetate
LD50 (Dermal): 2000 mg/kg bw rat
LD50 (Oral): 6482 mg/kg rat
LC50 (Inhalation vapours): 49,2 mg/l/4h rabbit

Isobutane
LC50 (Inhalation mists/powders): > 1442,738 mg/l/15min rat

Methanol
ATE (Dermal): 300 mg/kg estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)
ATE (Oral): 100 mg/kg estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)
LC50 (Inhalation vapours): > 87,6 mg/l/4h Rat
ATE (Inhalation mists/powders): 0,501 mg/l
(figure used for calculation of the acute toxicity estimate of the mixture)

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Excluded because the aerosol does not allow the accumulation of a significant amount of product in the mouth

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it has negative effects on the aquatic environment.

SECTION 12. Ecological information ... / >>

12.1. Toxicity

Hydrocarbons, C6, isoalkanes, <5% n-hexane

LC50 - for Fish	8,41 mg/l/96h
EC50 - for Crustacea	4,7 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 12 mg/l/72h
Chronic NOEC for Algae / Aquatic Plants	6,47 mg/l

Propane

LC50 - for Fish	85,82 mg/l/96h
EC50 - for Crustacea	41,82 mg/l/48h

Butane

LC50 - for Fish	> 24,11 mg/l/96h

Methyl acetate

LC50 - for Fish	300 mg/l/96h
EC50 - for Crustacea	1,027 g/l
EC50 - for Algae / Aquatic Plants	120 mg/l/72h
Chronic NOEC for Algae / Aquatic Plants	120 mg/l 72 h

Isobutane

LC50 - for Fish	> 24,11 mg/l/96h

Methanol

LC50 - for Fish	15,4 g/l/96h
Chronic NOEC for Fish	446,7 mg/l 28 days
Chronic NOEC for Crustacea	208 mg/l 21 days

12.2. Persistence and degradability

Hydrocarbons, C6, isoalkanes, <5% n-hexane
Rapidly degradable

Propane
Solubility in water 0,1 - 100 mg/l
Rapidly degradable
Global Warming Potential (GWP): 3. Ozone Depletion Potential (ODP): 0.

Butane
Solubility in water 0,1 - 100 mg/l
Rapidly degradable

Methyl acetate
Solubility in water 243500 mg/l
Rapidly degradable

Isobutane
Rapidly degradable

Methanol
Solubility in water 1000 - 10000 mg/l
Rapidly degradable

12.3. Bioaccumulative potential

Propane
Partition coefficient: n-octanol/water 1,09

Butane
Partition coefficient: n-octanol/water 1,09

SECTION 12. Ecological information ... / >>

Methyl acetate
Partition coefficient: n-octanol/water 0,18

Methanol
Partition coefficient: n-octanol/water -0,77
BCF 0,2

12.4. Mobility in soil

Hydrocarbons, C6, isoalkanes, <5% n-hexane
Partition coefficient: soil/water 1,78

Methyl acetate
Partition coefficient: soil/water 0,18

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.
Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.
Waste transportation may be subject to ADR restrictions.
The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.
CONTAMINATED PACKAGING
Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

Product residues are to be considered special hazardous waste.
Empty cans, even if completely emptied, must not be dispersed in the environment.
The aerosol container overheated to a temperature above 50 ° C may burst even if it contains a small residue of gas.
Disposal must take place in an authorized place and in compliance with the laws in force.
The transport of waste may be subject to ADR.
European waste catalog code (contaminated containers):
Aerosol as domestic waste is excluded from the application of the aforementioned rule.
The exhausted aerosol for professional / industrial use can be classified:
15.01.11 *: metallic packaging containing dangerous solid porous matrices, including empty pressure containers.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: UN 1950

14.2. UN proper shipping name

ADR / RID: AEROSOLS
IMDG: AEROSOLS
IATA: AEROSOLS, FLAMMABLE

SECTION 14. Transport information ... / >>

14.3. Transport hazard class(es)

ADR / RID:	Class: 2	Label: 2.1	
IMDG:	Class: 2	Label: 2.1	
IATA:	Class: 2	Label: 2.1	

14.4. Packing group

ADR / RID, IMDG, IATA: -

14.5. Environmental hazards

ADR / RID:	Environmentally Hazardous	
IMDG:	Marine Pollutant	
IATA:	NO	

For Air transport, environmentally hazardous mark is only mandatory for UN 3077 and UN 3082.

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: --	Limited Quantities: 1 lt	Tunnel restriction code: (D)
	Special provision: 190, 327, 344, 625		
IMDG:	EMS: F-D, S-U	Limited Quantities: 1 lt	
IATA:	Cargo:	Maximum quantity: 150 kg	Packaging instructions: 203
	Passengers:	Maximum quantity: 75 kg	Packaging instructions: 203
	Special provision:	A145, A167, A802	

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P3a-E2

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product
- Point 40

Contained substance
- Point 75
- Point 69 Methanol
  REACH Reg.: 01-2119433307-44-XXXX

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors
not applicable

Substances in Candidate List (Art. 59 REACH)
On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)
None

SECTION 15. Regulatory information ... / >>

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:
None

Substances subject to the Rotterdam Convention:
None

Substances subject to the Stockholm Convention:
None

Healthcare controls
Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1A	Flammable gas, category 1A
Aerosol 1	Aerosol, category 1
Aerosol 3	Aerosol, category 3
Flam. Liq. 2	Flammable liquid, category 2
Press. Gas (Liq.)	Liquefied gas
Press. Gas (Comp.)	Compressed gas
Press. Gas	Pressurised gas
Acute Tox. 3	Acute toxicity, category 3
STOT SE 1	Specific target organ toxicity - single exposure, category 1
Asp. Tox. 1	Aspiration hazard, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
STOT SE 2	Specific target organ toxicity - single exposure, category 2
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H225	Highly flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H370	Causes damage to organs.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H371	May cause damage to organs.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

LEGEND:
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%

SECTION 16. Other information ... / >>

- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)
27. Delegated Regulation (UE) 2024/2564 (XXII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:
The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.
This document must not be regarded as a guarantee on any specific product property.
The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.
Provide appointed staff with adequate training on how to use chemical products.

SECTION 16. Other information ... / >>

CALCULATION METHODS FOR CLASSIFICATION
Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.
Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.
Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:
The following sections were modified:
01 / 02 / 03 / 08 / 09 / 10 / 11 / 12 / 14 / 15 / 16.