

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: P300
Product name: UNIVERSAL CLEANER SOLVENT 400 ml AMBRO-SOL
UFI: EGA0-P0U8-A00Q-CPSD

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Universal spray cleaner

Identified Uses	Industrial	Professional	Consumer
Consumer	-	-	✓
Industrial Use	✓	-	-
Professional Use	-	✓	-

1.3. Details of the supplier of the safety data sheet

Name: AMBRO-SOL S.R.L. SB
Full address: Via per Pavone del Mella, 21
District and Country: 25020 Cigole (BS)
Italia
Tel.: +39 030 9959674
Fax: +39 030 959265
e-mail address of the competent person responsible for the Safety Data Sheet: regulatory@ambro-sol.com

1.4. Emergency telephone number

For urgent inquiries refer to

IT - Centro Antiveleni di Milano - Ospedale Niguarda: Tel. 02 66101029 (Italy)
AT - Vergiftungsinformationszentrale (VIZ): Tel. +43 01 406 4343 (Austria)
BE - Belgisch Antigifcentrum: Tel. 070 245245 (Belgium)
BG - НАЦИОНАЛЕН ЦЕНТЪР ПО ТОКСИКОЛОГИЯ: Tel. +359 2 9154 233 (Bulgaria)
HR - Centar za kontrolu otrovanja: Tel. +385 1 2348342 (Croatia)
CY - Τμήμα Επιθεώρησης Εργασίας (ΤΕΕ): Tel. 1401 (Cyprus)
CZ - Toxikologické informační středisko (TIS): Tel. +420 224 919 293 / +420 224 915 402 (Czech Republic)
DK - Giftlinjen: Ring 82 12 12 12 (Denmark)
EE - Mürgistusteabekeskus: Tel. 16662 (Estonia)
FI - Myrkytystietokeskus: Tel. 0800 147 111 / 09 471 977 (Finland)
FR - ORFILA (INRS): Tél. +33 (0) 1 45 42 59 59 (France)
DE - Giftnotruf der Charité Universitätsmedizin Berlin: Tel. +49 030 19240 (Germany)
GR - Κέντρο Δηλητηριάσεων: Τηλ. 210 7793777 (Greece)
HU - Egészségügyi Toxikológiai Tájékoztató Szolgálat (ETTSZ): Tel. +36 80 20 1199 (Hungary)
IS - Eitrunarmiðstöð: Tel. 543 2222 (Iceland)
IE - National Poisons Information Centre (NPIC): Tel. 01 8092566 / 01 8379964 (Republic of Ireland)
LV - Latvian Poisons Information Centre: Tel. +371 67042473 (Latvia)
LT - Apsinuodijimų Informacijos biuras: Tel. 8-5 236 2052 (Lithuania)
LU - Giftinformationszentrum: Tel. +352 8002 5500 (Luxembourg)
NL - Nationaal Vergiftigingen Informatie Centrum (NVIC): Tel. 030 274 88 88 (Netherlands)
NO - Giftinformasjonen: Tel. 22 9 13 00 (Norway)
PL - Pomorskie Centrum Toksykologii: Tel. +58 682 04 04 (Poland)
PT - Centro de Informação Antivenenos (CIAV): Tel. 800 250 250 (Portugal)
RO - Biroul RSI Si Informare Toxicologica: Tel. 021 318 36 06 (Romania)
SK - Národné Toxikologické informačné centrum (NTIC): Tel. 02 5477 4166 (Slovakia)
SI - Center za klinično toksikologijo in farmakologijo: Tel. 112 (Slovenia)

ES - Servicio de Información Toxicológica (SIT) España: Tel.+34 91 562 04 20 (Spain)
SE - Giftinformationscentralen: Tel. 112 (Sweden)
CH - Schweizerisches Toxikologisches Informationszentrum (STIZ): Tel. +41 145 (Switzerland)
GB - National Poisons Information Service (NPIS) Tel. 0344 892 0111 (United Kingdom)
Members of the Public: NHS 111 (England), NHS 24 (Scotland) or NHS Direct (Wales)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1	H222	Extremely flammable aerosol.
	H229	Pressurised container: may burst if heated.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.
Hazardous to the aquatic environment, chronic toxicity, category 2	H411	Toxic to aquatic life with long lasting effects.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH208	Contains: (R)-P-MENTHA-1,8-DIENE May produce an allergic reaction.

Precautionary statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251	Do not pierce or burn, even after use.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.
P501	Dispose of contents/container in accordance with local regulations.
P102	Keep out of reach of children.
P211	Do not spray on an open flame or other ignition source.

Contains: PROPAN-2-OL

SECTION 2. Hazards identification ... / >>

Hydrocarbons, C6, isoalkanes, <5% n-hexane
ETHYL ACETATE

Ingredients according to Regulation (EC) No. 648/2004

30% and more Aliphatic hydrocarbons

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
Hydrocarbons, C6, isoalkanes, <5% n-hexane INDEX 649-328-00-1	$58 \leq x < 59,5$	Flam. Liq. 2 H225, Asp. Tox. 1 H304, Skin Irrit. 2 H315, STOT SE 3 H336, Aquatic Chronic 2 H411, Classification note according to Annex VI to the CLP Regulation: P
EC 931-254-9 CAS 64742-49-0 REACH Reg. 012119484651-34-XXXX		
PROPANE INDEX 601-003-00-5	$15 \leq x < 16,5$	Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: U
EC 200-827-9 CAS 74-98-6 REACH Reg. 01-2119486944-21-0046		
PROPAN-2-OL INDEX 603-117-00-0	$15 \leq x < 16,5$	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336
EC 200-661-7 CAS 67-63-0 REACH Reg. 01-2119457558-25-XXXX		
BUTANE INDEX 601-004-00-0	$7 \leq x < 8,5$	Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: C, U
EC 203-448-7 CAS 106-97-8 REACH Reg. 01-2119474691-32-XXXX		
ETHYL ACETATE INDEX 607-022-00-5	$1,7 \leq x < 1,8$	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066
EC 205-500-4 CAS 141-78-6 REACH Reg. 01-2119475103-46-XXXX		
Isobutane INDEX 601-004-00-0	$1,2 \leq x < 1,3$	Flam. Gas 1A H220, Press. Gas H280
EC 200-857-2 CAS 75-28-5 REACH Reg. 01-2119485395-27-XXXX		

SECTION 3. Composition/information on ingredients ... / >>

(R)-P-MENTHA-1,8-DIENE

INDEX 601-096-00-2 0,05 ≤ x < 0,1

Flam. Liq. 3 H226, Asp. Tox. 1 H304, Skin Irrit. 2 H315, Skin Sens. 1B H317,
Aquatic Acute 1 H400 M=1, Aquatic Chronic 3 H412

EC 227-813-5

CAS 5989-27-5

REACH Reg. 01-2119529223-47-XXXX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants: 24,48 %

Hydrocarbons, C6, isoalkanes, <5% n-hexane

Hydrocarbons, C6, isoalkanes, <5% n-hexane: a complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C4 through C11 and boiling in the range of approximately minus 20Å ° C to 190Å ° C (-4Å ° F to 374Å ° F).

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably

SECTION 6. Accidental release measures ... / >>

equipped. Wear protective gloves / protective clothing / eye protection / face protection.

6.2. Environmental precautions

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

7.2. Conditions for safe storage, including any incompatibilities

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

CZE	Česká Republika	NAŘÍZENÍ VLÁDY ze dne 10. května 2021, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci
DEU	Deutschland	Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58
DNK	Danmark	Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019
ESP	España	Límites de exposición profesional para agentes químicos en España 2023
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France Décret n° 2021-1849 du 28 décembre 2021
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α' 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία"»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NOR	Norge	Forskrift om endring i forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og grenseverdier), 21. august 2018 nr. 1255
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
SVK	Slovensko	NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénnym a mutagénnym faktorom pri práci v znení

SECTION 8. Exposure controls/personal protection ... / >>

GBR	United Kingdom	neskorších predpisov
EU	OEL EU	EH40/2005 Workplace exposure limits (Fourth Edition 2020) Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2023

Hydrocarbons, C6, isoalkanes, <5% n-hexane

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
NDS/NDSch	POL	500		1500		

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers		Effects on workers					
	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Oral				1301				
				mg/kg bw/d				
Inhalation				1137				5306
				mg/m3				mg/m3
Skin				1377				13964
				mg/kg bw/d				mg/kg bw/d

PROPANE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	1800	1000	7200	4000	
MAK	DEU	1800	1000	7200	4000	
TLV	DNK	1800	1000			
VLA	ESP		1000			
TLV	GRC	1800	1000			
TLV	NOR	900	500			
NDS/NDSch	POL	1800				
TLV	ROU	1400	778	1800	1000	

SECTION 8. Exposure controls/personal protection ... / >>

PROPAN-2-OL

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	CZE	500	200	1000	400	
AGW	DEU	500	200	1000	400	
MAK	DEU	500	200	1000	400	
TLV	DNK	490	200			
VLA	ESP	500	200	1000	400	
VLEP	FRA			980	400	
TLV	GRC	500	200	1000	400	
AK	HUN	500	200	1000	400	SKIN
TLV	NOR	245	100			
TGG	NLD	650				
NDS/NDSch	POL	900		1200		SKIN
TLV	ROU	200	81	500	203	
NPEL	SVK	500	200	1000	400	
WEL	GBR	999	400	1250	500	
TLV-ACGIH		492	200	983	400	

Predicted no-effect concentration - PNEC

Normal value in fresh water	140,9	mg/l
Normal value in marine water	140,9	mg/l
Normal value for fresh water sediment	552	mg/kg/d
Normal value for marine water sediment	552	mg/kg/d
Normal value for water, intermittent release	140,9	mg/l
Normal value of STP microorganisms	2,251	g/l
Normal value for the food chain (secondary poisoning)	160	mg/kg
Normal value for the terrestrial compartment	28	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral	VND	VND	VND		VND	VND	VND	VND
Inhalation	VND	VND	VND		VND	VND	VND	500
Skin	VND	VND	VND		VND	VND	VND	888

mg/kg bw/d

BUTANE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	2400	1000	9600	4000	
MAK	DEU	2400	1000	9600	4000	
TLV	DNK	1200	500			
VLA	ESP		1000			Gases
VLEP	FRA	1900	800			
TLV	GRC	2350	1000			
AK	HUN	2350		9400		
TLV	NOR	600	250			
TGG	NLD	1430				
NDS/NDSch	POL	1900		3000		
WEL	GBR	1450	600	1810	750	
WEL	GBR		4			RESP
TLV-ACGIH				1000		

SECTION 8. Exposure controls/personal protection ... / >>

ETHYL ACETATE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m ³	ppm	mg/m ³	ppm	
TLV	CZE	700	191,1	900	245,7	
AGW	DEU	730	200	1460	400	
MAK	DEU	750	200	1500	400	
TLV	DNK	540	150	1468	400	E
VLA	ESP	734	200	1468	400	
VLEP	FRA	734	200	1468	400	
TLV	GRC	734	200	1468	400	
AK	HUN	734	200	1468	400	
VLEP	ITA	734	200	1468	400	
TLV	NOR	734	200			
TGG	NLD	734		1468		
VLE	PRT	734	200	1468	400	
NDS/NDSch	POL	734		1468		
TLV	ROU	734	200	1468	400	
NPEL	SVK	734	200	1468	400	
WEL	GBR	734	200	1468	400	
OEL	EU	734	200	1468	400	
TLV-ACGIH		1441	400			

Predicted no-effect concentration - PNEC

Normal value in fresh water	240	µg/l
Normal value in marine water	24	µg/l
Normal value for fresh water sediment	1,15	µg/kg
Normal value for marine water sediment	115	µg/kg
Normal value for water, intermittent release	1,65	mg/l
Normal value of STP microorganisms	650	mg/l
Normal value for the food chain (secondary poisoning)	200	mg/kg
Normal value for the terrestrial compartment	148	µg/kg/d
Normal value for the atmosphere	NPI	

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	4,5 mg/kg				
Inhalation	734 mg/kg	734 mg/kg	367 mg/m ³	367 mg/m ³	1468 mg/m ³	1468 mg/m ³	734 mg/m ³	734 mg/m ³
Skin			VND	37 mg/kg				63 mg/kg

Isobutane

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m ³	ppm	mg/m ³	ppm	
TLV-ACGIH			800			

SECTION 8. Exposure controls/personal protection ... / >>

(R)-P-MENTHA-1,8-DIENE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	28	5	112	20	SKIN
MAK	DEU	28	5	112	20	SKIN
VLA	ESP	168	30			SKIN
TLV	NOR	140	25			

Predicted no-effect concentration - PNEC

Normal value in fresh water	14	µg/L
Normal value in marine water	1,4	µg/L
Normal value for fresh water sediment	3,85	mg/kg/d
Normal value for marine water sediment	385	µg/kg/d
Normal value of STP microorganisms	1,8	mg/l
Normal value for the food chain (secondary poisoning)	133	mg/kg
Normal value for the terrestrial compartment	763	µg/kg/d

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation	NPI	NPI	NPI	66,7 mg/m3	NPI	NPI	NPI	16,6 mg/m3
Skin	NPI	NPI	NPI	4,8 mg/kg bw/d	VND	NPI	VND	9,5 mg/kg bw/d

Citral

Predicted no-effect concentration - PNEC

Normal value in fresh water	6,78	µg/l
Normal value in marine water	678	ng/l
Normal value for fresh water sediment	125	µg/kg/d
Normal value for marine water sediment	12,5	µg/kg/d
Normal value for water, intermittent release	67,8	µg/l
Normal value of STP microorganisms	1,6	mg/l
Normal value for the terrestrial compartment	20,9	µg/kg/d
Normal value for the atmosphere	NPI	

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		NPI		600 µg/kg bw/d				
Inhalation		NPI		2,7 mg/m3		NPI		9 mg/m3
Skin		NPI	140 µg/cm2	1 mg/kg bw/d		NPI	140 µg/cm2	1,7 mg/kg bw/d

SECTION 8. Exposure controls/personal protection ... / >>

2,6-dimethyloct-7-en-2-ol

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,0278	mg/l
Normal value in marine water	0,00278	mg/l
Normal value for fresh water sediment	0,594	mg/kg
Normal value for marine water sediment	0,0594	mg/kg
Normal value for water, intermittent release	0,0278	mg/l
Normal value of STP microorganisms	10	mg/l
Normal value for the food chain (secondary poisoning)	0,111	mg/kg
Normal value for the terrestrial compartment	0,103	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral								12,5 mg/kg bw/d
Inhalation				21,7 mg/m3				73,5 mg/m3
Skin							12,5 mg/kg bw/d	20,8 mg/kg bw/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

None required.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	aerosol	
Colour	colourless	
Odour	aromatic	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	flammable gas	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	< 0 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	not available	Reason for missing data: substance/mixture is

SECTION 9. Physical and chemical properties ... / >>

Kinematic viscosity	0,700 mm ² /s SIO D445 (ASTM D445)	non-polar/aprotic (eg: an organic solvent mixture)
Solubility	slightly soluble	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	0,63 ± 0,67 kg/l	Temperature: 20 °C
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

VOC (Directive 2010/75/EU)	99,24 % - 659,94 g/litre
Explosive properties	not applicable
Oxidising properties	not applicable
Remarks	Il prodotto può essere aggressivo su

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

ETHYL ACETATE

It slowly decomposes into acetic acid and ethanol due to the action of light, air and water.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

ETHYL ACETATE

Risk of explosion on contact with: alkaline metals,hydrides,oleum.May react violently with: fluorine,strong oxidising agents,chlorosulphuric acid,potassium tert-butoxide.Forms explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating.

ETHYL ACETATE

Avoid exposure to: light,sources of heat,naked flames.

10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

ETHYL ACETATE

Incompatible with: acids,bases,strong oxidants,chlorosulphuric acid.

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information _____

SECTION 11. Toxicological information ... / >>

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:	Not classified (no significant component)
ATE (Oral) of the mixture:	Not classified (no significant component)
ATE (Dermal) of the mixture:	Not classified (no significant component)

Hydrocarbons, C6, isoalkanes, <5% n-hexane	
LD50 (Dermal):	> 2000 mg/kg bw rabbit
LD50 (Oral):	> 2000 mg/kg bw rat
LC50 (Inhalation vapours):	> 25 mg/l/4h air (rat)

PROPANE	
LC50 (Inhalation mists/powders):	800000 ppm 15 min

PROPAN-2-OL	
LD50 (Dermal):	16,4 ml/kg rabbit
LD50 (Oral):	5840 mg/kg bw Rat
LC50 (Inhalation vapours):	> 10000 ppm/6h Rat

BUTANE	
LC50 (Inhalation mists/powders):	> 1442,738 mg/l/15min rat

ETHYL ACETATE	
LD50 (Dermal):	20000 mg/kg bw rabbit
LD50 (Oral):	11,3 mg/kg bw rat
LC50 (Inhalation mists/powders):	> 22,5 mg/l/6h rat

Isobutane	
LC50 (Inhalation mists/powders):	> 1442,738 mg/l/15min rat

(R)-P-MENTHA-1,8-DIENE	
LD50 (Oral):	2000 mg/kg rat

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.

Contains:

(R)-P-MENTHA-1,8-DIENE

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

SECTION 11. Toxicological information ... / >>

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Excluded because the aerosol does not allow the accumulation of a significant amount of product in the mouth

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity

(R)-P-MENTHA-1,8-DIENE

LC50 - for Fish	590 µg/l/96h
EC50 - for Crustacea	307 µg/l/48h
EC50 - for Algae / Aquatic Plants	267 µg/l/72h
Chronic NOEC for Fish	80 µg/l 28 days
Chronic NOEC for Crustacea	65 µg/l 21 days
Chronic NOEC for Algae / Aquatic Plants	90 µg/l 48 h

BUTANE

LC50 - for Fish	> 24,11 mg/l/96h
-----------------	------------------

PROPANE

LC50 - for Fish	85,82 mg/l/96h
EC50 - for Crustacea	41,82 mg/l/48h

PROPAN-2-OL

LC50 - for Fish	9,6 g/l/96h
-----------------	-------------

ETHYL ACETATE

LC50 - for Fish	230 mg/l/96h
EC50 - for Algae / Aquatic Plants	100 mg/l/72h
Chronic NOEC for Fish	9,65 mg/l 32 days
Chronic NOEC for Crustacea	2,4 mg/l 21 days

Hydrocarbons, C6, isoalkanes, <5% n-hexane

LC50 - for Fish	8,41 mg/l/96h
EC50 - for Crustacea	4,7 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 12 mg/l/72h
Chronic NOEC for Algae / Aquatic Plants	6,47 mg/l

Isobutane

LC50 - for Fish	> 24,11 mg/l/96h
-----------------	------------------

12.2. Persistence and degradability

PROPANE

Global Warming Potential (GWP): 3. Ozone Depletion Potential (ODP): 0.

SECTION 12. Ecological information ... / >>

(R)-P-MENTHA-1,8-DIENE	
Solubility in water	0,1 - 100 mg/l
Rapidly degradable	
BUTANE	
Solubility in water	0,1 - 100 mg/l
Rapidly degradable	
PROPANE	
Solubility in water	0,1 - 100 mg/l
Rapidly degradable	
PROPAN-2-OL	
Rapidly degradable	Readily biodegradable (50%)
ETHYL ACETATE	
Solubility in water	> 10000 mg/l
Rapidly degradable	
Hydrocarbons, C6, isoalkanes, <5% n-hexane	
Rapidly degradable	
Isobutane	
Rapidly degradable	

12.3. Bioaccumulative potential

(R)-P-MENTHA-1,8-DIENE	
Partition coefficient: n-octanol/water	4,38
BCF	1022
BUTANE	
Partition coefficient: n-octanol/water	1,09
PROPANE	
Partition coefficient: n-octanol/water	1,09
PROPAN-2-OL	
Partition coefficient: n-octanol/water	0,05
ETHYL ACETATE	
Partition coefficient: n-octanol/water	0,68
BCF	30

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

SECTION 13. Disposal considerations ... / >>

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

Product residues are to be considered special hazardous waste.

Empty cans, even if completely emptied, must not be dispersed in the environment.

The aerosol container overheated to a temperature above 50 ° C may burst even if it contains a small residue of gas.

Disposal must take place in an authorized place and in compliance with the laws in force.

The transport of waste may be subject to ADR.

European waste catalog code (contaminated containers):

Aerosol as domestic waste is excluded from the application of the aforementioned rule.

The exhausted aerosol for professional / industrial use can be classified:

15.01.11 *: metallic packaging containing dangerous solid porous matrices, including empty pressure containers.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: UN 1950

14.2. UN proper shipping name

ADR / RID: AEROSOLS, FLAMMABLE

IMDG: AEROSOLS

IATA: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es)

ADR / RID: Class: 2 Label: 2.1



IMDG: Class: 2 Label: 2.1



IATA: Class: 2 Label: 2.1



14.4. Packing group

ADR / RID, IMDG, IATA: -

14.5. Environmental hazards

ADR / RID: Environmentally Hazardous



IMDG: Marine Pollutant



IATA: NO

For Air transport, environmentally hazardous mark is only mandatory for UN 3077 and UN 3082.

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: --	Limited Quantities: 1 L	Tunnel restriction code: (D)
	Special provision: 190, 327, 344, 625		
IMDG:	EMS: F-D, S-U	Limited Quantities: 1 L	
IATA:	Cargo:	Maximum quantity: 150 Kg	Packaging instructions: 203
	Passengers:	Maximum quantity: 75 Kg	Packaging instructions: 203
	Special provision:	A145, A167, A802	

SECTION 16. Other information ... / >>

H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)

SECTION 16. Other information ... / >>

19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 08 / 10 / 11 / 12 / 14.