

Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: S159
 Product name: XT10 400 ml AMBRO-SOL
 UFI: D720-30K4-X006-VWU6

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Aerosol product 10 functions in 1: unlocking, lubricating, protective, penetrating, degreasing, anti-corrosion, anti-scurf, waterproof, dissolves rust, resistant to high temperatures.

Identified Uses	Industrial	Professional	Consumer
Consumer	-	-	✓
Industrial Use	✓	-	-
Professional Use	-	✓	-

1.3. Details of the supplier of the safety data sheet

Name: AMBRO-SOL SRL SOCIETA' BENEFIT
 Full address: Via per Pavone del Mella n.21
 District and Country: 25020 Cigole (BS)
 Italia
 Tel. +39 030 9959674
 Fax +39 030 959265

e-mail address of the competent person responsible for the Safety Data Sheet

regulatory@ambro-sol.com

1.4. Emergency telephone number

For urgent inquiries refer to

IT - Centro Antiveleni di Milano - Ospedale Niguarda: Tel. 02 66101029 (Italy)
 AT - Vergiftungsinformationszentrale (VIZ): Tel. +43 01 406 4343 (Austria)
 BE - Belgisch Antigifcentrum: Tel. 070 245245 (Belgium)
 BG - НАЦИОНАЛЕН ЦЕНТЪР ПО ТОКСИКОЛОГИЯ: Tel. +359 2 9154 233 (Bulgaria)
 HR - Centar za kontrolu otrovanja: Tel. +385 1 2348342 (Croatia)
 CY - Τμήμα Επιθεώρησης Εργασίας (TEE): Tel. 1401 (Cyprus)
 CZ - Toxikologické informační středisko (TIS): Tel. +420 224 919 293 / +420 224 915 402 (Czech Republic)
 DK - Giftlinjen: Ring 82 12 12 12 (Denmark)
 EE - Mürgistusteabekeskus: Tel. 16662 (Estonia)
 FI - Myrkytystietokeskus: Tel. 0800 147 111 / 09 471 977 (Finland)
 FR - ORFILA (INRS): Tél. +33 (0) 1 45 42 59 59 (France)
 DE - Giftnotruf der Charité Universitätsmedizin Berlin: Tel. +49 030 19240 (Germany)
 GR - Κέντρο Δηλητηριάσεων: Τηλ. 210 7793777 (Greece)
 HU - Egészségügyi Toxikológiai Tájékoztató Szolgálat (ETTSZ): Tel. +36 80 20 1199 (Hungary)
 IS - Eitrunarmiðstöð: Tel. 543 2222 (Iceland)
 IE - National Poisons Information Centre (NPIC): Tel. 01 8092566 / 01 8379964 (Republic of Ireland)
 LV - Latvian Poisons Information Centre: Tel. +371 67042473 (Latvia)
 LT - Apsinuodijimų Informacijos biuras: Tel. 8-5 236 2052 (Lithuania)
 LU - Giftinformationszentrum: Tel. +352 8002 5500 (Luxembourg)
 NL - Nationaal Vergiftigingen Informatie Centrum (NVIC): Tel. 030 274 88 88

(Netherlands)

NO - Gifinformaties: Tel. 22 9 13 00 (Norway)

PL - Pomorskie Centrum Toksykologii: Tel. +58 682 04 04 (Poland)

PT - Centro de Informação Antivenenos (CIAV): Tel. 800 250 250 (Portugal)

RO - Biroul RSI Si Informare Toxicologica: Tel. 021 318 36 06 (Romania)

SK - Národné Toxikologické informačné centrum (NTIC): Tel. 02 5477 4166 (Slovakia)

SI - Center za klinično toksikologijo in farmakologijo: Tel. 112 (Slovenia)

ES - Servicio de Información Toxicológica (SIT) España: Tel.+34 91 562 04 20 (Spain)

SE - Giftinformationscentralen: Tel. 112 (Sweden)

CH - Schweizerisches Toxikologisches Informationszentrum (STIZ): Tel. +41 145 (Switzerland)

GB - National Poisons Information Service (NPIS) Tel. 0344 892 0111 (United Kingdom)

Members of the Public: NHS 111 (England), NHS 24 (Scotland) or NHS Direct (Wales)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1

H222

Extremely flammable aerosol.

H229

Pressurised container: may burst if heated.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Danger

Hazard statements:

H222

Extremely flammable aerosol.

H229

Pressurised container: may burst if heated.

EUH066

Repeated exposure may cause skin dryness or cracking.

Precautionary statements:

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251

Do not pierce or burn, even after use.

P410+P412

Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.

P102

Keep out of reach of children.

P211

Do not spray on an open flame or other ignition source.

P501 Dispose of contents/container in accordance with local regulations.

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics		
INDEX -	$47 \leq x < 51$	Asp. Tox. 1 H304, EUH066
EC 918-481-9		
CAS -		
REACH Reg. 01-2119457273-39-XXXX		
Distillates (petroleum), hydrotreated light naphthenic		
INDEX 649-466-00-2	$15 \leq x < 19$	Asp. Tox. 1 H304, Classification note according to Annex VI to the CLP Regulation: L Asp. Tox. 1 H304: \geq 40%
EC 265-156-6		
CAS 64742-53-6		
REACH Reg. 01-2119480375-34-XXXX		
Propane		
INDEX 601-003-00-5	$11 \leq x < 15$	Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: U
EC 200-827-9		
CAS 74-98-6		
REACH Reg. 01-2119486944-21-0046		
Butane		
INDEX 601-004-00-0	$5 \leq x < 7$	Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: C, U
EC 203-448-7		
CAS 106-97-8		
REACH Reg. 01-2119474691-32-XXXX		
Benzenesulfonic acid, mono-C19-28-alkyl derivs., sodium salts		
INDEX -	$1 \leq x < 3$	Aquatic Chronic 4 H413
EC 274-265-8		
CAS 70024-73-6		
Polytetrafluorethylene (PTFE)		
INDEX -	$1 \leq x < 3$	
EC 618-337-2		

CAS 9002-84-0

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants: 19,30 %

Distillates (petroleum), hydrotreated light naphthenic

* DECLL (CLP): This substance is classified according to note L of Annex VI of CE regulation 1272/2008. Classification as a carcinogen is not necessary if one can demonstrate that the substance contains less than 3% DMSO extract according to IP 346 measurement "Determination of polycyclic aromatics in unused lubricating base oils and petroleum fractions without asphaltene - dimethyl sulfoxide extraction ", Institute of Petroleum, London. This note only applies to certain petroleum-derived compound substances contained in Part 3.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always

wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

6.2. Environmental precautions

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

7.2. Conditions for safe storage, including any incompatibilities

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α' 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών

AMBRO-SOL SRL SOCIETA' BENEFIT

Revision nr. 17

Dated 22/12/2022

S159 - XT10 400 ml AMBRO-SOL

Printed on 22/12/2022

Page n. 6/17

Replaced revision:16 (Dated: 31/08/2021)

HUN	Magyarország	<p>2017/2398/EE, 2019/130/EE και 2019/983/EE «για την τροποποίηση της οδηγίας 2004/37/EK ``σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία``» Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai köröki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről Decreto Legislativo 9 Aprile 2008, n.81 Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénym a mutagénym faktorom pri práci v znení neskorších predpisov EH40/2005 Workplace exposure limits (Fourth Edition 2020) ACGIH 2021</p>
ITA	Italia	
PRT	Portugal	
POL	Polska	
SVK	Slovensko	
GBR	United Kingdom TLV-ACGIH	

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Predicted no-effect concentration - PNEC

Normal value for the atmosphere

NPI

Distillates (petroleum), hydrotreated light naphthenic

Predicted no-effect concentration - PNEC

Normal value for the food chain (secondary poisoning)

9,33

mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Chronic systemic	Effects on workers			
	Acute local	Acute systemic	Chronic local		Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation								5.4 mg/m3 8h

Propane

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	1800	1000	7200	4000	
MAK	DEU	1800	1000	7200	4000	
VLA	ESP		1000			
TLV	GRC	1800	1000			
NDS/NDSch	POL	1800				

Butane

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	2400	1000	9600	4000	
MAK	DEU	2400	1000	9600	4000	
VLA	ESP		1000			Gases
VLEP	FRA	1900	800			
TLV	GRC	2350	1000			
AK	HUN	2350		9400		
NDS/NDSch	POL	1900		3000		
WEL	GBR	1450	600	1810	750	

AMBRO-SOL SRL SOCIETA' BENEFIT

Revision nr. 17

Dated 22/12/2022

S159 - XT10 400 ml AMBRO-SOL

Printed on 22/12/2022

Page n. 7/17

Replaced revision:16 (Dated: 31/08/2021)

WEL	GBR	4			RESP
TLV-ACGIH				1000	
Polytetrafluorethylene (PTFE)					
Threshold Limit Value					
Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
TLV-ACGIH		10			POLVERI
Isobutane					
Threshold Limit Value					
Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
TLV-ACGIH			800		
Distillates (petroleum), hydrotreated heavy naphthenic					
Threshold Limit Value					
Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
VLA	ESP	5		10	
TLV	GRC	5			
AK	HUN	5			
VLEP	ITA	5			INHAL
VLE	PRT	5		10	
NDS/NDSch	POL	5			
NPEL	SVK	1		3	15
Predicted no-effect concentration - PNEC					
Normal value for the food chain (secondary poisoning)				9,33	mg/kg

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

HAND PROTECTION

None required.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Properties	Value	Information
Appearance	aerosol	
Colour	straw yellow	
Odour	characteristic of solvent	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	flammable gas	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	< 0 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	not available	Reason for missing data: substance/mixture is non-polar/aprotic (eg: an organic solvent mixture)
Kinematic viscosity	< 8 mm ² /s 40°C	
Solubility	insoluble in water	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	0,76 ÷ 0,80 kg/l	Temperature: 20 °C
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

VOC (Directive 2010/75/EU) 89,43 % - 697,51 g/litre

Explosive properties not applicable
Oxidising properties not applicable

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

Avoid overheating.

Polytetrafluorethylene (PTFE)

Avoid exposure to: >400 °C.

10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

Polytetrafluorethylene (PTFE)

May react dangerously if exposed to: metals in powder form from 370 ° C.

10.6. Hazardous decomposition products

Polytetrafluorethylene (PTFE)

May develop: hydrofluoric acid, carbonyl fluoride, tetrafluoroethylene, hexafluoropropylene, perfluoroisobutylene.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:	Not classified (no significant component)
ATE (Oral) of the mixture:	Not classified (no significant component)
ATE (Dermal) of the mixture:	Not classified (no significant component)

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

LD50 (Dermal):	2000 mg/kg bw rat
LD50 (Oral):	> 5000 mg/kg bw rat
LC50 (Inhalation vapours):	> 4 mg/l/4h rat

Distillates (petroleum), hydrotreated light naphthenic

LD50 (Dermal):	3500 mg/kg bw rabbit
LD50 (Oral):	5000 mg/kg bw rat
LC50 (Inhalation vapours):	3,85 mg/l/4h rat

Propane

LC50 (Inhalation mists/powders):	800000 ppm 15 min
----------------------------------	-------------------

Butane

LC50 (Inhalation mists/powders):	> 1442,738 mg/l/15min rat
----------------------------------	---------------------------

SKIN CORROSION / IRRITATION

Repeated exposure may cause skin dryness or cracking.

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Excluded because the aerosol does not allow the accumulation of a significant amount of product in the mouth

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

Hydrocarbons, C10-C13, n-alkanes,
isoalkanes, cyclics, <2% aromatics
Chronic NOEC for Algae / Aquatic Plants 1000 mg/l 72 hours

Butane
LC50 - for Fish > 24,11 mg/l/96h

Propane
LC50 - for Fish 85,82 mg/l/96h
EC50 - for Crustacea 41,82 mg/l/48h

12.2. Persistence and degradability

Propane
Global Warming Potential (GWP): 3. Ozone Depletion Potential (ODP): 0.
Distillates (petroleum), hydrotreated light
naphthenic
Degradability: information not available

Echa sources
Hydrocarbons, C10-C13, n-alkanes,
isoalkanes, cyclics, <2% aromatics
Rapidly degradable
But failing the 10-day window (100%).
Butane

Solubility in water 0,1 - 100 mg/l

Rapidly degradable
Propane

Solubility in water 0,1 - 100 mg/l

Rapidly degradable
Benzenesulfonic acid, mono-C19-28-alkyl
derivs., sodium salts
Degradability: information not available

12.3. Bioaccumulative potential

Butane
Partition coefficient: n-octanol/water 1,09

Propane
Partition coefficient: n-octanol/water 1,09

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

Product residues are to be considered special hazardous waste.

Empty cans, even if completely emptied, must not be dispersed in the environment.

The aerosol container overheated to a temperature above 50 ° C may burst even if it contains a small residue of gas.

Disposal must take place in an authorized place and in compliance with the laws in force.

The transport of waste may be subject to ADR.

European waste catalog code (contaminated containers):

Aerosol as domestic waste is excluded from the application of the aforementioned rule.

The exhausted aerosol for professional / industrial use can be classified:

15.01.11 *: metallic packaging containing dangerous solid porous matrices, including empty pressure containers.

SECTION 14. Transport information**14.1. UN number or ID number**

ADR / RID, IMDG, IATA: 1950

14.2. UN proper shipping name

ADR / RID: AEROSOLS

IMDG: AEROSOLS

IATA: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es)

ADR / RID: Class: 2 Label: 2.1



IMDG: Class: 2 Label: 2.1



IATA: Class: 2 Label: 2.1



14.4. Packing group

ADR / RID, IMDG, IATA: -

14.5. Environmental hazards

ADR / RID: NO

IMDG: NO

IATA: NO

14.6. Special precautions for user

ADR / RID: HIN - Kemler: --

Limited Quantities: 1 L

Tunnel restriction code: (D)

IMDG: Special provision: -
EMS: F-D, S-U

Limited Quantities: 1 L

IATA: Cargo:

Maximum quantity: 150 Kg

Packaging instructions: 203

Pass.:

Maximum quantity: 75 Kg

Packaging instructions: 203

Special provision:

A145, A167, A802

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P3a

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 40

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1A	Flammable gas, category 1A
Aerosol 1	Aerosol, category 1
Aerosol 3	Aerosol, category 3
Press. Gas (Liq.)	Liquefied gas
Asp. Tox. 1	Aspiration hazard, category 1
Aquatic Chronic 4	Hazardous to the aquatic environment, chronic toxicity, category 4
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H413	May cause long lasting harmful effects to aquatic life.
EUH066	Repeated exposure may cause skin dryness or cracking.

S159 - XT10 400 ml AMBRO-SOL**LEGEND:**

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2019/521 (XII Atp. CLP)
 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
 17. Regulation (EU) 2019/1148
 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

AMBRO-SOL SRL SOCIETA' BENEFIT

Revision nr. 17

Dated 22/12/2022

S159 - XT10 400 ml AMBRO-SOL

Printed on 22/12/2022

Page n. 17/17

Replaced revision:16 (Dated: 31/08/2021)

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

01 / 08 / 09 / 15.