Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **V400/PAST**
Product name **ANTIRUST PRIMER 400 ml AMBRO-SOL**

UFI : **UTS1-X08V-2000-MXFF**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Spray paint for surface treatment**

Identified Uses	Industrial	Professional	Consumer
Consumer	-	-	✓
Industrial Use	✓	-	-
Professional Use	-	✓	-

1.3. Details of the supplier of the safety data sheet

Name **AMBRO-SOL S.R.L. SB**
Full address **Via per Pavone del Mella, 21 - 23**
District and Country **25020 Cigole (BS)**
Italia
Tel. +39 030 9959674

e-mail address of the competent person responsible for the Safety Data Sheet **regulatory@ambro-sol.com**

Supplier: **Importer: Ambro-Sol UK Ltd, Express Park, Bridgwater, Somerset, TA6 4RR, UK, info@ambro-sol.co.uk, phone number / emergency number +44 1278 552999**

1.4. Emergency telephone number

For urgent inquiries refer to

IT - Centro Antiveleni di Milano - Ospedale Niguarda: Tel. 02 66101029 (Italy)
AT - Vergiftungsinformationszentrale (VIZ): Tel. +43 01 406 4343 (Austria)
BE - Belgisch Antigifcentrum: Tel. 070 245245 (Belgium)
BG - НАЦИОНАЛЕН ЦЕНТЪР ПО ТОКСИКОЛОГИЯ: Tel. +359 2 9154 233 (Bulgaria)
HR - Centar za kontrolu otrovanja: Tel. +385 1 2348342 (Croatia)
CY - Τμήμα Επιθεώρησης Εργασίας (TEE): Tel. 1401 (Cyprus)
CZ - Toxikologické informační středisko (TIS): Tel. +420 224 919 293 / +420 224 915 402 (Czech Republic)
DK - Giftlinjen: Ring 82 12 12 12 (Denmark)
EE - Mürgistusteabekeskus: Tel. 16662 (Estonia)
FI - Myrkytystietokeskus: Tel. 0800 147 111 / 09 471 977 (Finland)
FR - ORFILA (INRS): Tél. +33 (0) 1 45 42 59 59 (France)
DE - Giftnotruf der Charité Universitätsmedizin Berlin: Tel. +49 030 19240 (Germany)
GR - Κέντρο Δηλητηριάσεων: Τηλ. 210 7793777 (Greece)
HU - Egészségügyi Toxikológiai Tájékoztató Szolgálat (ETTSZ): Tel. +36 80 20 1199 (Hungary)
IS - Eitrunarmiðstöð: Tel. 543 2222 (Iceland)
IE - National Poisons Information Centre (NPIC): Tel. 01 8092566 / 01 8379964 (Republic of Ireland)
LV - Latvian Poisons Information Centre: Tel. +371 67042473 (Latvia)
LT - Apsinuodijimų Informacijos biuras: Tel. 8-5 236 2052 (Lithuania)
LU - Giftinformationszentrum: Tel. +352 8002 5500 (Luxembourg)
NL - Nationaal Vergiftigingen Informatie Centrum (NVIC): Tel. 030 274 88 88 (Netherlands)
NO - Giftinformasjonen: Tel. 22 9 13 00 (Norway)
PL - Pomorskie Centrum Toksykologii: Tel. +58 682 04 04 (Poland)
PT - Centro de Informação Antivenenos (CIAV): Tel. 800 250 250 (Portugal)
RO - Biroul RSI Si Informare Toxicologica: Tel. 021 318 36 06 (Romania)
SK - Národné Toxikologické informačné centrum (NTIC): Tel. 02 5477 4166

(Slovakia)
SI - Center za klinično toksikologijo in farmakologijo: Tel. 112 (Slovenia)
ES - Servicio de Información Toxicológica (SIT) España: Tel.+34 91 562 04 20 (Spain)
SE - Giftinformationscentralen: Tel. 112 (Sweden)
CH - Schweizerisches Toxikologisches Informationszentrum (STIZ): Tel. +41 145 (Switzerland)
GB - National Poisons Information Service (NPIS) Tel. 0344 892 0111 (United Kingdom)
Members of the Public: NHS 111 (England), NHS 24 (Scotland) or NHS Direct (Wales)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.
Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1	H222	Extremely flammable aerosol.
	H229	Pressurised container: may burst if heated.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal word: Danger

Hazard statements:

H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Precautionary statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251	Do not pierce or burn, even after use.
P410+P412	Protect from sunlight. Do no expose to temperatures exceeding 50°C / 122°F.
P501	Dispose of contents/container in accordance with local regulations.
P102	Keep out of reach of children.
P101	If medical advice is needed, have product container or label at hand.
P211	Do not spray on an open flame or other ignition source.

SECTION 2. Hazards identification ... / >>

Contains: Methyl acetate
N-butyl acetate
Xylene
1-methyl-2-methoxyethyl acetate

VOC (Directive 2004/42/EC) :
Special finishes - All types.
VOC given in g/litre of product in a ready-to-use condition : 658,19
Limit value: 840,00

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification		x = Conc. %	Classification (EC) 1272/2008 (CLP)
Methyl acetate			
INDEX	*607-021-00-X*	35 ≤ x < 36,5	**Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066**
EC	*201-185-2*		
CAS	*79-20-9*		
REACH Reg.	*01-2119459211-47-XXXX*		
Propane			
INDEX	*601-003-00-5*	19 ≤ x < 20,5	**Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: U**
EC	*200-827-9*		
CAS	*74-98-6*		
REACH Reg.	*01-2119486944-21-0046*		
Butane			
INDEX	*601-004-00-0*	9 ≤ x < 10,5	**Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: C, U**
EC	*203-448-7*		
CAS	*106-97-8*		
REACH Reg.	*01-2119474691-32-XXXX*		
N-butyl acetate			
INDEX	*607-025-00-1*	8,5 ≤ x < 10	**Flam. Liq. 3 H226, STOT SE 3 H336, EUH066**
EC	*204-658-1*		
CAS	*123-86-4*		
REACH Reg.	*01-2119485493-29-XXXX*		
Xylene			
INDEX	*601-022-00-9*	7 ≤ x < 8,5	**Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, STOT SE 3 H336, Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP Regulation: C**
EC	*215-535-7*		**LD50 Dermal: >1700 mg/kg, ATE Inhalation mists/powders: 1,5 mg/l**
CAS	*1330-20-7*		
REACH Reg.	*01-2119488216-32-XXXX*		
Isobutane			
INDEX	*601-004-00-0*	1,5 ≤ x < 1,6	**Flam. Gas 1A H220, Press. Gas H280**
EC	*200-857-2*		
CAS	*75-28-5*		
REACH Reg.	*01-2119485395-27-XXXX*		
Methanol			
INDEX	*603-001-00-X*	1 ≤ x < 1,1	**Flam. Liq. 2 H225, Acute Tox. 3 H301, Acute Tox. 3 H311, Acute Tox. 3 H331, STOT SE 1 H370**
EC	*200-659-6*		**STOT SE 2 H371: ≥ 3% - < 10%**
CAS	*67-56-1*		**ATE Oral: 100 mg/kg, ATE Dermal: 300 mg/kg, ATE Inhalation mists/powders: 0,501 mg/l**
REACH Reg.	*01-2119433307-44-XXXX*		

SECTION 3. Composition/information on ingredients ... / >>

1-methyl-2-methoxyethyl acetate

INDEX	*607-195-00-7*	1 ≤ x < 1,1	**Flam. Liq. 3 H226, STOT SE 3 H336**
EC	*203-603-9*		
CAS	*108-65-6*		
REACH Reg.	*01-2119475791-29-XXXX*		

Bis (Orthophosphate) of Trizinco

INDEX	*030-011-00-6*	0,3 ≤ x < 0,35	**Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1**
EC	*231-944-3*		
CAS	*7779-90-0*		
REACH Reg.	*01-2119485044-40-0001*		

Ethylbenzene

INDEX	*601-023-00-4*	0,3 ≤ x < 0,35	**Flam. Liq. 2 H225, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Aquatic Chronic 3 H412**
EC	*202-849-4*		**ATE Inhalation mists/powders: 1,5 mg/l**
CAS	*100-41-4*		
REACH Reg.	*01-2119489370-35-XXXX*		

Quartz

INDEX		0 < x < 0,05	**STOT RE 2 H373**
EC	*238-878-4*		
CAS	*14808-60-7*		
REACH Reg.	*Esente secondo l'allegato V.7*		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.
Percentage of propellants: 30,50 %

Isobutane
Note Isobutane: This product contains < 0.1 % w/w 1,3 butadiene (EINECS 203-450-8). This product should be considered as non-carcinogenic and non-mutagenic

SECTION 4. First aid measures

4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.
In case of more severe symptoms, ask for immediate medical aid.
EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.
SKIN: Take off contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice. Avoid further contact with contaminated clothing.
INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.
INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

Call a POISON CENTER or doctor/physician if you feel unwell.

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT
The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.
UNSUITABLE EXTINGUISHING EQUIPMENT
None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE
If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION
Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.
SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS
Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

6.2. Environmental precautions

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

7.2. Conditions for safe storage, including any incompatibilities

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

1-methyl-2-methoxyethyl acetate
Store in an inert atmosphere, sheletered from moisture because it hydrolises easily.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.28 от 2 Април 2024г.)
CZE	Česká Republika	NAŘÍZENÍ VLÁDY ze dne 18. října 2023, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	WirkungDosisNOAELMAK-und BAT-Werte-Liste 2024 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe
DNK	Danmark	BEK nr 291 af 19/03/2024 (Historisk) Bekendtgørelse om grænseværdier for stoffer og materialer (kemiske agenser) i arbejdsmiljøet
ESP	España	Límites de exposición profesional para agentes químicos en España 2024
EST	Eesti	Ohtlike kemikaalide ja neid sisaldavate materjalide kasutamise töötervishoiu ja tööohutuse nõuded ning töökeskkonna keemiliste ohutegurite piirnormid 2024
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en FranceDécret n° 2021-1849 du 28 décembre 2021
FIN	Suomi	HTP-VÄRDEN 2020. Koncentrationer som befunnits skadliga. SOCIAL - OCH HÄLSOVÅRDSMINISTERIETS PUBLIKATIONER 2020:25
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ ''σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιγόνους παράγοντες κατά την εργασία''»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
LTU	Lietuva	Jsakymas dėl lietuvos higienos normos hn 23:2011 „cheminių medžiagų profesinio poveikio ribiniai dydžiai. Matavimo ir poveikio vertinimo bendrieji reikalavimai“ patvirtinimo
LVA	Latvija	Grozījumi Ministru kabineta 2007. gada 15. maija noteikumos Nr. 325 "Darba aizsardzības prasības saskarē ar ķīmiskajām vielām darba vietās" Oficiālās publikācijas Nr.: 2024/65.2
NOR	Norge	Forskrift om endring i forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og grenseverdier), 21. 10. april 2024 kl. 13.55
NLD	Nederland	Regeling van de Minister van Sociale Zaken en Werkgelegenheid van 13 mei2024, nr. 2024-0000092805, tot wijziging van deArbeidsomstandighedenregeling in verband met de implementatie vanRichtlijn 2022/431
PRT	Portugal	Decreto-Lei n.º 102/2024, de 4 de dezembro. Sumário: Transpõe para a ordem jurídica interna a Diretiva (UE) 2022/431, relativa à proteção dos trabalhadores contra riscos ligados à exposição a agentes cancerígenos ou mutagénicos e procede à quarta alteração
POL	Polska	ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 24 czerwca 2024 r. zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
ROU	România	HOTĂRÂRE nr. 179 din 28 februarie 2024 pentru modificarea şi completarea Hotărârii Guvernului nr. 1.093/2006 privind stabilirea cerinţelor minime de securitate şi sănătate pentru protecţia lucrătorilor împotriva riscurilor legate de expunerea la agenţi ca
SWE	Sverige	Arbetsmiljöverkets föreskrifter och allmänna råd (AFS 2023:14) om gränsvärden för luftvägsexponering i arbetsmiljön
SVK	Slovensko	121_2024 Z. z. Nariadenie vlády o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénnym, mutagénnym alebo reprodukčne toxickým faktorom pri práci
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti rakotvornim, mutagenim ali reprotoksičnim snovem pri delu. Ljubljana, četrtek 4. 4. 2024
TUR	Türkiye	Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733; 20.10.2023 / 32345.
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	ACGIH	ACGIH 2025

SECTION 8. Exposure controls/personal protection ... / >>

Xylene

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
TLV	BGR	221	50	442	100	SKIN	
TLV	CZE	200	45,33	400	90,66	SKIN	
AGW	DEU	220	50	440	100	SKIN	
MAK	DEU	220	50	440	100	SKIN	
TLV	DNK	109	25	442	100	SKIN	E
VLA	ESP	221	50	442	100	SKIN	
TLV	EST	200	50	450	100	SKIN	
VLEP	FRA	221	50	442	100	SKIN	
HTP	FIN	220	50	440	100	SKIN	
TLV	GRC	435	100	650	150		
AK	HUN	221	50	442	100	SKIN	
VLEP	ITA	221	50	442	100	SKIN	
RD	LTU	221	50	442	100	SKIN	
RV	LVA	221	50	442	100	SKIN	
TLV	NOR	108	25			SKIN	
TGG	NLD	210		442		SKIN	
VLE	PRT	221	50	442	100	SKIN	
NDS/NDSCh	POL	100		200		SKIN	
TLV	ROU	221	50	442	100	SKIN	
NGV/KGV	SWE	221	50	442	100	SKIN	
NPEL	SVK	221	50	442	100	SKIN	
MV	SVN	221	50	442	100	SKIN	
ESD	TUR	221	50	442	100	SKIN	
WEL	GBR	220	50	441	100	SKIN	
OEL	EU	221	50	442	100	SKIN	
ACGIH			20				

Predicted no-effect concentration - PNEC

Normal value in fresh water	327	µg/l
Normal value in marine water	327	µg/l
Normal value for fresh water sediment	12,46	mg/kg/d
Normal value for marine water sediment	12,46	mg/kg/d
Normal value of STP microorganisms	6,58	mg/l
Normal value for the terrestrial compartment	2,31	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				5 mg/kg bw/d				
Inhalation	260 mg/m3	260 mg/m3	65 mg/m3	65.3 mg/m3	442 mg/m3	442 mg/m3	221 mg/m3	221 mg/m3
Skin				125 mg/kg bw/d		LOW		212 mg/kg bw/d

Silicon dioxide

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	1		8		INHAL
MAK	DEU	1		0,16	8	INHAL
MAK	DEU	0,02		0,16		RESP
TLV	EST	2				RESP
RV	LVA	1				
MV	SVN	4				INHAL

Health - Derived no-effect level - DNEL / DMEL

	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation								4 mg/m3

SECTION 8. Exposure controls/personal protection ... / >>

1-methyl-2-methoxyethyl acetate

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
TLV	BGR	275	50	550	100	SKIN	
TLV	CZE	275	50	550	100	SKIN	
AGW	DEU	270	50	270	50		
MAK	DEU	270	50	270	50		
TLV	DNK	275	50	550	100	SKIN	E
VLA	ESP	275	50	550	100	SKIN	
TLV	EST	275	50	550	100	SKIN	
VLEP	FRA	275	50	550	100	SKIN	
HTP	FIN	270	50	550	100	SKIN	
TLV	GRC	275	50	550	100		
AK	HUN	275	50	550	100		
VLEP	ITA	275	50	550	100	SKIN	
RD	LTU	250	50	400	75	SKIN	
RV	LVA	275	50	550	100	SKIN	
TLV	NOR	270	50			SKIN	
TGG	NLD	550					
VLE	PRT	275	50	550	100	SKIN	
NDS/NDSCh	POL	260		520		SKIN	
TLV	ROU	275	50	550	100	SKIN	
NGV/KGV	SWE	275	50	550	100	SKIN	
NPEL	SVK	275	50	550	100	SKIN	
MV	SVN	275	50	550	100	SKIN	
ESD	TUR	275	50	550	100	SKIN	
WEL	GBR	274	50	548	100	SKIN	
OEL	EU	275	50	550	100	SKIN	

Predicted no-effect concentration - PNEC

Normal value in fresh water	635	µg/l
Normal value in marine water	63,5	µg/l
Normal value for fresh water sediment	3,29	mg/kg/d
Normal value for marine water sediment	329	µg/kg/d
Normal value of STP microorganisms	100	mg/l
Normal value for the terrestrial compartment	290	µg/kg soil dw

Health - Derived no-effect level - DNEL / DMEL

	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		NPI		36 mg/kg bw/d				
Inhalation	NPI	NPI	33 mg/m3	33 mg/m3	550 mg/m3	NPI	NPI	275 mg/m3
Skin	NPI	NPI	NPI	320 mg/kg bw/d	NPI	NPI	NPI	796 mg/kg bw/d

SECTION 8. Exposure controls/personal protection ... / >>

Quartz

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	DNK	0,3		0,6		
VLA	ESP		0,05			RESP
TLV	EST	0,1				RESP
VLEP	FRA	0,1				RESP
VLEP	ITA	0,1				RESP
RD	LTU	0,1				
TLV	NOR	0,1				RESP
TGG	NLD	0,075				RESP
VLE	PRT	0,05				RESP
NDS/NDSCh	POL	0,1				RESP
TLV	ROU	0,1				RESP
NGV/KGV	SWE	0,1				RESP
NPEL	SVK	0,1				RESP
MV	SVN	0,05				RESP
OEL	EU	0,1				RESP
ACGIH		0,025				RESP

Butane

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	1900				
AGW	DEU	2400	1000	9600	4000	
MAK	DEU	2400	1000	9600	4000	
TLV	DNK	1200	500	2400	1000	
VLA	ESP		1000			Gases
TLV	EST	1500	800			
VLEP	FRA	1900	800			
HTP	FIN	1900	800	2400	1000	
TLV	GRC	2350	1000			
AK	HUN	2350		9400		
RV	LVA	300				
TLV	NOR	600	250			
TGG	NLD	1430				
NDS/NDSCh	POL	1900		3000		
NPEL	SVK	2400	1000			
MV	SVN	2400	1000	9600	4000	
WEL	GBR	1450	600	1810	750	
WEL	GBR		4			RESP
ACGIH					1000	

Propane

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	1800				
AGW	DEU	1800	1000	7200	4000	
MAK	DEU	1800	1000	7200	4000	
TLV	DNK	1800	1000	3200	2000	
VLA	ESP		1000			
TLV	EST	1800	1000			
HTP	FIN	1500	800	2000	1100	
TLV	GRC	1800	1000			
RV	LVA	1800	1000			
TLV	NOR	900	500			
NDS/NDSCh	POL	1800				
TLV	ROU	1400	778	1800	1000	
MV	SVN	1800	1000	7200	4000	
ESD	TUR	1800	1000			

SECTION 8. Exposure controls/personal protection ... / >>

Ethylbenzene

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
TLV	BGR	435		545		SKIN	
TLV	CZE	200	45,33	500	113,32	SKIN	
AGW	DEU	88	20	176	40	SKIN	
MAK	DEU	88	20	176	40	SKIN	
TLV	DNK	217	50	434	100	SKIN	E
VLA	ESP	441	100	884	200	SKIN	
TLV	EST	442	100	884	200	SKIN	
VLEP	FRA	88,4	20	442	100	SKIN	
HTP	FIN	220	50	880	200	SKIN	
TLV	GRC	435	100	545	125		
AK	HUN	442	100	884	200	SKIN	
VLEP	ITA	442	100	884	200	SKIN	
RD	LTU	442	100	884	200	SKIN	
RV	LVA	442	100	884	200	SKIN	
TLV	NOR	20	5			SKIN	
TGG	NLD	215		430		SKIN	
VLE	PRT	442	100	884	200	SKIN	
NDS/NDSCh	POL	200		400		SKIN	
TLV	ROU	442	100	884	200	SKIN	
NGV/KGV	SWE	220	50	884	200	SKIN	
NPEL	SVK	442	100	884	200	SKIN	
MV	SVN	442	100	884	200	SKIN	
ESD	TUR	442	100	884	200	SKIN	
WEL	GBR	441	100	552	125	SKIN	
OEL	EU	442	100	884	200	SKIN	
ACGIH		87	20				

Predicted no-effect concentration - PNEC

Normal value in fresh water	100	µg/l
Normal value in marine water	55	µg/l
Normal value for fresh water sediment	13,7	mg/kg/d
Normal value for marine water sediment	1,37	mg/kg/d
Normal value for water, intermittent release	55	µg/l
Normal value of STP microorganisms	9,6	mg/l
Normal value for the food chain (secondary poisoning)	20	mg/kg
Normal value for the terrestrial compartment	2,68	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		NPI		1,6 mg/kg bw/d				1,6
Inhalation	NPI	VND	NPI	15 mg/m3	293 mg/m3	VND	NPI	77 mg/m3
Skin		NPI		NPI	NPI	NPI	NPI	180 mg/kg bw/d

SECTION 8. Exposure controls/personal protection ... / >>

Methanol

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
TLV	BGR	260	200			SKIN	
TLV	CZE	250	188	1000	751	SKIN	
AGW	DEU	130	100	260	200	SKIN	
MAK	DEU	130	100	260	200	SKIN	
TLV	DNK	260	200	520	400	SKIN	E
VLA	ESP	266	200			SKIN	
TLV	EST	250	200	350	250	SKIN	
VLEP	FRA	260	200			SKIN	
HTP	FIN	270	200	330	250	SKIN	
TLV	GRC	260	200	325	250		
AK	HUN	260	200			SKIN	
VLEP	ITA	260	200			SKIN	
RD	LTU	260	200			SKIN	
RV	LVA	260	200			SKIN	
TLV	NOR	130	100			SKIN	
TGG	NLD	133				SKIN	
VLE	PRT	260	200			SKIN	
NDS/NDSCh	POL	100		300		SKIN	
TLV	ROU	260	200			SKIN	
NGV/KGV	SWE	250	200	350 (C)	250 (C)	SKIN	
NPEL	SVK	260	200			SKIN	
MV	SVN	260	200	1040	800	SKIN	
ESD	TUR	260	200			SKIN	
WEL	GBR	266	200	333	250	SKIN	
OEL	EU	260	200				
ACGIH		262	200	328	250	SKIN	

Predicted no-effect concentration - PNEC

Normal value in fresh water	20,8	mg/l
Normal value in marine water	2,08	mg/l
Normal value for fresh water sediment	77	mg/kg/d
Normal value for marine water sediment	7,7	mg/kg/d
Normal value for water, intermittent release	1,54	g/l
Normal value of STP microorganisms	100	mg/l
Normal value for the terrestrial compartment	100	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		8 mg/kg bw/d		8 mg/kg bw/d				
Inhalation	50 mg/m3	50 mg/m3	50 mg/m3	50 mg/m3	260 mg/m3	260 mg/m3	260 mg/m3	260 mg/m3
Skin		8 mg/kg bw/d		8 mg/kg bw/d		40 mg/kg bw/d		40 mg/kg bw/d

SECTION 8. Exposure controls/personal protection ... / >>

Methyl acetate

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	CZE	600	195	800	260	
AGW	DEU	620	200	1240	400	
MAK	DEU	310	100	1240	400	
TLV	DNK	455	150	910	300	
VLA	ESP	616	200	770	250	
TLV	EST	450	150	900	300	
VLEP	FRA	610	200	760	250	SKIN
HTP	FIN	610	200	770	250	
TLV	GRC	610	200	760	250	
AK	HUN	310	200	1240	400	SKIN
RD	LTU	450	150	900	300	
RV	LVA	100				
TLV	NOR	305	100			
TGG	NLD	100				
NDS/NDSCh	POL	250		600		
TLV	ROU	200	63	600	188	
NGV/KGV	SWE	450	150	900 (C)	300 (C)	
NPEL	SVK	310	100	770	250	
MV	SVN	620	200	1240	400	
ESD	TUR	610	200			
WEL	GBR	616	200	770	250	
ACGIH		606	200	757	250	

Predicted no-effect concentration - PNEC

Normal value in fresh water	120	µg/l
Normal value in marine water	12	µg/l

Health - Derived no-effect level - DNEL / DMEL

	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		NPI		44 mg/kg bw/d				
Inhalation	VND	VND	152 mg/m3		VND	VND	305 mg/m3	610 mg/m3
Skin			NPI	44 mg/kg bw/d	NPI	VND	NPI	88 mg/kg bw/d

SECTION 8. Exposure controls/personal protection ... / >>

N-butyl acetate

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	241	50	723	150	
TLV	CZE	241	50	723	150	
AGW	DEU	300	62	600	124	
MAK	DEU	480	100	960	200	
TLV	DNK	241	50	723	150	E
VLA	ESP	241	50	723	150	
TLV	EST	241	50	723	150	
VLEP	FRA	241	50	723	150	
TLV	GRC	710	150	950	200	
AK	HUN	241	50	723	150	
VLEP	ITA	241	50	723	150	
RD	LTU	241	50	723	150	
RV	LVA	241	50	723	150	
TLV	NOR		75			
TGG	NLD	150				
VLE	PRT	241	50	723	150	
NDS/NDSCh	POL	240		720		
TLV	ROU	241	50	723	150	
NGV/KGV	SWE	241	50	723 (C)	150 (C)	
NPEL	SVK	241	50	723	150	
MV	SVN	241	50	723	150	
ESD	TUR	241	50	723	150	
WEL	GBR	724	150	966	200	
OEL	EU	241	50	723	150	
ACGIH			50		150	

Predicted no-effect concentration - PNEC

Normal value in fresh water	180	µg/l
Normal value in marine water	18	µg/l
Normal value for fresh water sediment	981	µg/kg/d
Normal value for marine water sediment	98,1	µg/kg/d
Normal value of STP microorganisms	35,6	mg/l
Normal value for the terrestrial compartment	90,3	µg/kg/d

Health - Derived no-effect level - DNEL / DMEL

	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		2 mg/kg bw/d		2 mg/kg bw/d		2		2
Inhalation	300 mg/m3	300 mg/m3	35,7 mg/m3	12 mg/m3	600 mg/m3	600 mg/m3	300 mg/m3	48 mg/m3
Skin	NPI	6 mg/kg bw/d	NPI	3,4 mg/kg bw/d	NPI	11 mg/kg bw/d	NPI	7 mg/kg bw/d

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
MAK	DEU	300	50	600	100	
NDS/NDSCh	POL	300		900		

SECTION 8. Exposure controls/personal protection ... / >>

Bis (Orthophosphate) of Trizinco

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
MAK	DEU	2		4		INHAL	Als Zn
MAK	DEU	0,1		0,4		RESP	Als Zn
NPEL	SVK	2				INHAL	
NPEL	SVK	0,1				RESP	

Predicted no-effect concentration - PNEC

Normal value in fresh water	20,6	µg/l
Normal value in marine water	6,1	µg/l
Normal value for fresh water sediment	117,8	mg/kg/d
Normal value for marine water sediment	56,5	mg/kg/d
Normal value of STP microorganisms	100	µg/l
Normal value for the terrestrial compartment	35,6	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		NPI		830 µg/kg bw/d				
Inhalation	NPI	NPI	NPI	2,5 mg/m3	NPI	NPI	NPI	5 mg/m3
Skin	NPI	NPI	NPI	83 mg/kg bw/d	NPI	NPI	NPI	83 mg/kg bw/d

SECTION 8. Exposure controls/personal protection ... / >>

Zinc oxide

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	5		10		като цинк
TLV	CZE	2		5		Jako Zn
MAK	DEU	2		4		INHAL
MAK	DEU	0,1		0,4		RESP
TLV	DNK	4		8		Som Zn
VLA	ESP	2		10		
TLV	EST	5				
VLEP	FRA	5				
VLEP	FRA	10				RESP
HTP	FIN	2		10		
TLV	GRC	5		10		
AK	HUN	5				
RD	LTU	5				
RV	LVA	0,5				
TLV	NOR	5				
NDS/NDSCh	POL	5		10		INHAL Na Zn
TLV	ROU	5		10		Fumuri
NGV/KGV	SWE	5				
NPEL	SVK	1		1		RESP
MV	SVN	5		20		RESP
ACGIH		2		10		RESP

Predicted no-effect concentration - PNEC

Normal value in fresh water	20,6	µg/l
Normal value in marine water	6,1	µg/l
Normal value for fresh water sediment	117,8	mg/kg/d
Normal value for marine water sediment	56,5	mg/kg/d
Normal value of STP microorganisms	100	µg/l
Normal value for the terrestrial compartment	35,6	mg/kg/d
Normal value for the atmosphere	NPI	

Health - Derived no-effect level - DNEL / DMEL

	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral	NPI	NPI	NPI	830 µg/kg bw/d				
Inhalation	NPI	NPI	NPI	2,5 mg/m3	NPI	NPI	500 µg/m3	5 mg/m3
Skin	NPI	NPI	NPI	83 mg/kg bw/d	NPI	NPI	NPI	83 mg/kg bw/d

Isobutane

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
ACGIH			800			

SECTION 8. Exposure controls/personal protection ... / >>

Reaction mass of ethylbenzene and xylene								
Predicted no-effect concentration - PNEC								
Normal value in fresh water						327	µg/l	
Normal value in marine water						327	µg/l	
Normal value for fresh water sediment						12,46	mg/kg/d	
Normal value for marine water sediment						12,46	mg/kg/d	
Normal value for water, intermittent release						327	µg/l	
Normal value of STP microorganisms						6,58	mg/l	
Normal value for the terrestrial compartment						2,31	mg/kg/d	
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				1,6 mg/kg bw/d				
Inhalation				14,8 mg/m3	289 mg/m3			77 mg/m3
Skin				108 mg/kg bw/d				180 mg/kg bw/d

Reaction mass of ethylbenzene and m-xylene and p-xylene								
Predicted no-effect concentration - PNEC								
Normal value in fresh water						0,327	mg/l	
Normal value in marine water						0,327	mg/l	
Normal value for fresh water sediment						12,46	mg/kg/d	
Normal value for marine water sediment						12,46	mg/kg/d	
Normal value for water, intermittent release						0,327	mg/l	
Normal value of STP microorganisms						6,58	mg/l	
Normal value for the terrestrial compartment						2,31	mg/kg/d	
Normal value for the atmosphere						0,327	mg/l	
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				1,6 mg/kg bw/d				
Inhalation				14,8 mg/m3	289 mg/m3			77 mg/m3
Skin				108 mg/kg bw/d				180 mg/kg bw/d

Talc								
Predicted no-effect concentration - PNEC								
Normal value in fresh water						597,97	mg/l	
Normal value in marine water						141,26	mg/l	
Normal value for fresh water sediment						31,33	mg/kg/d	
Normal value for marine water sediment						3,13	mg/kg/d	
Normal value for water, intermittent release						597,97	mg/l	
Normal value for the atmosphere						10	mg/m3	
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		160 mg/kg bw/d		160 mg/kg bw/d				
Inhalation	1,8 mg/m3	1,08 mg/m3	1,8 mg/m3	1,08 mg/m3	3,6 mg/m3	2,16 mg/m3	3,6 mg/m3	2,16 mg/m3
Skin			2,27 mg/cm2	2,16 mg/kg bw/d			4,54 mg/cm2	43,2 mg/kg bw/d

SECTION 8. Exposure controls/personal protection ... / >>

Strontium Hydrogen Phosphate

Health - Derived no-effect level - DNEL / DMEL

	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0,430 mg/kg bw/d				
Inhalation				1,51 mg/m3				5,1 mg/m3
Skin				0,430 mg/kg bw/d				0,720 mg/kg bw/d

Propylidintrimethanol

Health - Derived no-effect level - DNEL / DMEL

	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0,34 mg/kg bw/d				
Inhalation				0,58 mg/m3				3,3 mg/m3
Skin				0,34 mg/kg bw/d				0,94 mg/kg bw/d

Legend:
(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.
VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.
When choosing personal protective equipment, ask your chemical substance supplier for advice.
Personal protective equipment must be CE marked, showing that it complies with applicable standards.
Provide an emergency shower with face and eye wash station.
HAND PROTECTION
None required.
SKIN PROTECTION
Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.
EYE PROTECTION
Wear airtight protective goggles (see standard EN ISO 16321).
RESPIRATORY PROTECTION
Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).
ENVIRONMENTAL EXPOSURE CONTROLS
The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.
Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	aerosol	
Colour	White - Transparent - Gray - Red	
Odour	characteristic of solvent	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	flammable gas	
Lower explosive limit	not available	

SECTION 9. Physical and chemical properties ... / >>

Upper explosive limit		not available		
Flash point	<	0	°C	
Auto-ignition temperature		not available		
Decomposition temperature		not available		
pH		not available		Reason for missing data:substance/mixture is non-polar/aprotic (eg: an organic solvent mixture)
Kinematic viscosity		not available		
Solubility		insoluble in water		
Partition coefficient: n-octanol/water		not available		
Vapour pressure		not available		
Density and/or relative density		0,78	kg/l	Temperature: 20 °C
Relative vapour density		not available		
Particle characteristics		not applicable		

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

VOC (Directive 2004/42/EC) :	84,39 %	-	658,19	g/litre
Explosive properties	not applicable			
Oxidising properties	not applicable			

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

1-methyl-2-methoxyethyl acetate
Stable in normal conditions of use and storage.On contact with: strong oxidising agents.
With the air it may slowly develop peroxides that explode with an increase in temperature.

N-butyl acetate
Decomposes on contact with: water.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

Xylene
Stable in normal conditions of use and storage.Reacts violently with: strong oxidants,strong acids,nitric acid,perchlorates.May form explosive mixtures with: air.
1-methyl-2-methoxyethyl acetate
May react violently with: oxidising substances,strong acids,alkaline metals.
Ethylbenzene
Reacts violently with: strong oxidants.Attacks various types of plastic materials.May form explosive mixtures with: air.
N-butyl acetate
Risk of explosion on contact with: strong oxidising agents.May react dangerously with: alkaline hydroxides,potassium tert-butoxide.Forms explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating.

N-butyl acetate
Avoid exposure to: moisture,sources of heat,naked flames.

10.5. Incompatible materials

SECTION 10. Stability and reactivity ... / >>

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

1-methyl-2-methoxyethyl acetate
Incompatible with: oxidising substances,strong acids,alkaline metals.
N-butyl acetate
Incompatible with: water,nitrates,strong oxidants,acids,alkalis,zinc.

10.6. Hazardous decomposition products

Ethylbenzene
May develop: methane,styrene,hydrogen,ethane.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.
It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Bis (Orthophosphate) of Trizinco
With LD50 values that systematically exceed 2000 mg / kg bw (body weight), slightly soluble compounds such as trizinc bis (orthophosphate) (LD50 Ã ©> 5000) detect at low level of acute toxicity
by ingestion, not resulting in a classification for acute toxicity by ingestion. The bis (orthophosphate) of trizinc has a low acute inhalation toxicity (example, LC50 values of >5.7 mg / L / 4H), do not result in classification for acute inhalation toxicity.

Metabolism, toxicokinetics, mechanism of action and other information

1-methyl-2-methoxyethyl acetate
The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

Information on likely routes of exposure

N-butyl acetate
WORKERS: inhalation; contact with the skin.

Xylene
WORKERS: inhalation; contact with the skin.
POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

Methanol
WORKERS: inhalation; contact with the skin.
POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

1-methyl-2-methoxyethyl acetate
WORKERS: inhalation; contact with the skin.

Ethylbenzene
WORKERS: inhalation; contact with the skin.
POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

N-butyl acetate
In humans, the substance's vapours cause irritation of the eyes and nose. In the event of repeated exposure, skin irritation, dermatitis (dryness and cracking of the skin) and keratitis appear.

Xylene
Toxic action on the central nervous system (encephalopathies); irritant action on the skin, conjunctiva, cornea and respiratory system.

Methanol
The minimum lethal dose for humans by ingestion is considered to be in the range from 300 to 1000 mg/kg. Ingestion of 4-10 ml of the substance may cause permanent blindness in adult humans (IPCS).

1-methyl-2-methoxyethyl acetate
Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

SECTION 11. Toxicological information ... / >>

Ethylbenzene
As the counterparts of benzene, may have an acute effect on the central nervous system, with depression, narcosis, often preceded by dizziness and associated with headache (Ispesl). Is irritating for skin, conjunctiva and respiratory tract.

Interactive effects

N-butyl acetate
A case of acute intoxication been reported involving a 33 year old worker while cleaning a tank with a preparation containing xylenes, butyl acetate and ethylene glycol acetate. The person had irritation of the conjunctiva and upper respiratory tract, drowsiness and motor coordination disorders, which disappeared within 5 hours. The symptoms are attributed to poisoning by mixed xylenes and butyl acetate, with a possible synergistic effect responsible for the neurological effects. Cases of vacuolar keratitis are reported in workers exposed to a mixture of butyl acetate and isobutanol vapours, but with uncertainty concerning the responsibility of a particular solvent (INRC, 2011).

Xylene
Alcohol intake interferes with the metabolism of the substance, inhibiting it. Consumption of ethanol (0.8 g / kg) before a 4-hour exposure to xylenes vapors (145 and 280 ppm) causes a 50% decrease in the excretion of metilippuric acid, while the blood concentration of xylenes rises about 1.5-2 times. At the same time, there is an increase in the secondary side effects of ethanol. The metabolism of xylenes is enhanced by phenobarbital and 3-methyl-colanthrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with glycine, which results in a decrease in urinary excretion of metilippuric acid. Other industrial products can interfere with the metabolism of xylenes.

ACUTE TOXICITY

ATE (Inhalation - mists / powders) of the mixture:	> 5 mg/l
ATE (Oral) of the mixture:	>2000 mg/kg
ATE (Dermal) of the mixture:	>2000 mg/kg

Methyl acetate

LD50 (Dermal):	2000 mg/kg bw rat
LD50 (Oral):	6482 mg/kg rat
LC50 (Inhalation vapours):	49,2 mg/l/4h rabbit

Propane

LC50 (Inhalation mists/powders):	800000 ppm 15 min

Butane

LC50 (Inhalation mists/powders):	> 1442,738 mg/l/15min rat

N-butyl acetate

LD50 (Dermal):	> 5000 mg/kg rabbit
LD50 (Oral):	> 10000 mg/kg Rat
LC50 (Inhalation vapours):	0,74 mg/l/4h Rat

Xylene

LD50 (Dermal):	> 1700 mg/kg rabbit
LD50 (Oral):	> 3000 mg/kg rat
LC50 (Inhalation vapours):	5000 ppm/4h rat
ATE (Inhalation mists/powders):	1,5 mg/l (figure used for calculation of the acute toxicity estimate of the mixture)

Isobutane

LC50 (Inhalation mists/powders):	> 1442,738 mg/l/15min rat

Methanol

ATE (Dermal):	300 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
ATE (Oral):	100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
LC50 (Inhalation vapours):	> 87,6 mg/l/4h Rat
ATE (Inhalation mists/powders):	0,501 mg/l (figure used for calculation of the acute toxicity estimate of the mixture)

1-methyl-2-methoxyethyl acetate

LD50 (Dermal):	> 5000 mg/kg Rat
LD50 (Oral):	> 5000 mg/kg Rat
LC50 (Inhalation vapours):	1805,05 ppm LC0 (4 h) rat

SECTION 11. Toxicological information ... / >>

Bis (Orthophosphate) of Trizinco

LD50 (Dermal):	522 mg/kg rat
LD50 (Oral):	> 5000 mg/kg Rat - Wistar
LC50 (Inhalation mists/powders):	> 5,7 mg/l Rat

Ethylbenzene

LD50 (Dermal):	15354 mg/kg Rabbit
LD50 (Oral):	3500 mg/kg Rat
LC50 (Inhalation vapours):	17,2 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Causes skin irritation
Repeated exposure may cause skin dryness or cracking.

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

Xylene
Classified in group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).
The US Environmental Protection Agency (EPA) claims that "the data were found to be inadequate for an assessment of carcinogenic potential."

Ethylbenzene
Classified in Group 2B (possible human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 2000).
Classified in Group D (not classifiable as a human carcinogen) by the US Environmental Protection Agency (EPA) - (US EPA file on-line 2014).

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Excluded because the aerosol does not allow the accumulation of a significant amount of product in the mouth

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity

SECTION 12. Ecological information ... / >>

Methyl acetate

LC50 - for Fish	300 mg/l/96h
EC50 - for Crustacea	1,027 g/l
EC50 - for Algae / Aquatic Plants	120 mg/l/72h
Chronic NOEC for Algae / Aquatic Plants	120 mg/l 72 h

Propane

LC50 - for Fish	85,82 mg/l/96h
EC50 - for Crustacea	41,82 mg/l/48h

Butane

LC50 - for Fish	> 24,11 mg/l/96h

N-butyl acetate

LC50 - for Fish	18 mg/l/96h
EC50 - for Crustacea	32 mg/l/48h
EC50 - for Algae / Aquatic Plants	246 mg/l/72h
Chronic NOEC for Crustacea	23,2 mg/l 21 days
Chronic NOEC for Algae / Aquatic Plants	105 mg/l 72 h

Isobutane

LC50 - for Fish	> 24,11 mg/l/96h

Methanol

LC50 - for Fish	15,4 g/l/96h
Chronic NOEC for Fish	446,7 mg/l 28 days
Chronic NOEC for Crustacea	208 mg/l 21 days

1-methyl-2-methoxyethyl acetate

LC50 - for Fish	> 100 mg/l/96h
EC50 - for Crustacea	> 100 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 100 mg/l/72h
Chronic NOEC for Fish	> 10 mg/l 14 days
Chronic NOEC for Crustacea	100 mg/l
Chronic NOEC for Algae / Aquatic Plants	1 g/l 4 days

Bis (Orthophosphate) of Trizinco

LC50 - for Fish	0,78 mg/l/96h Pimephales promelas
EC50 - for Crustacea	0,86 mg/l/48h Daphnia magna
Chronic NOEC for Fish	720 µg/l 84 days
Chronic NOEC for Crustacea	1,71 mg/l 48 h
Chronic NOEC for Algae / Aquatic Plants	300 µg/l 3 months

Ethylbenzene

LC50 - for Fish	4,65 mg/l/96h
EC50 - for Crustacea	2,1 mg/l/48h
EC50 - for Algae / Aquatic Plants	5,15 mg/l/72h
Chronic NOEC for Fish	3,3 mg/l 4 days
Chronic NOEC for Crustacea	960 µg/l 7 days
Chronic NOEC for Algae / Aquatic Plants	3,95 mg/l 4 days

12.2. Persistence and degradability

Methyl acetate

Solubility in water	243500 mg/l

Rapidly degradable

Propane

Solubility in water	0,1 - 100 mg/l

Rapidly degradable

Global Warming Potential (GWP): 3. Ozone Depletion Potential (ODP): 0.

Butane

Solubility in water	0,1 - 100 mg/l

Rapidly degradable

SECTION 12. Ecological information ... / >>

N-butyl acetate
Solubility in water 5,3 g/l
Rapidly degradable

Xylene
Solubility in water 100 - 1000 mg/l
Rapidly degradable

Isobutane
Rapidly degradable

Methanol
Solubility in water 1000 - 10000 mg/l
Rapidly degradable

1-methyl-2-methoxyethyl acetate
Solubility in water > 10000 mg/l
Rapidly degradable
Easily biodegradable. It is rapidly oxidized into the air by photochemical reaction.

Bis (Orthophosphate) of Trizinco
Solubility in water 2,7 mg/l
Degradability: information not available

Ethylbenzene
Solubility in water 1000 - 10000 mg/l
Rapidly degradable

12.3. Bioaccumulative potential

Methyl acetate
Partition coefficient: n-octanol/water 0,18

Propane
Partition coefficient: n-octanol/water 1,09

Butane
Partition coefficient: n-octanol/water 1,09

N-butyl acetate
Partition coefficient: n-octanol/water 2,3
BCF 15,3

Xylene
Partition coefficient: n-octanol/water 3,12
BCF 25,9

Methanol
Partition coefficient: n-octanol/water -0,77
BCF 0,2

1-methyl-2-methoxyethyl acetate
Partition coefficient: n-octanol/water 1,2

Ethylbenzene
Partition coefficient: n-octanol/water 3,6

12.4. Mobility in soil

Methyl acetate
Partition coefficient: soil/water 0,18

N-butyl acetate
Partition coefficient: soil/water < 3

Xylene

SECTION 12. Ecological information ... / >>

Partition coefficient: soil/water 2,73

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.
Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.
Waste transportation may be subject to ADR restrictions.
The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.
CONTAMINATED PACKAGING
Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

Product residues are to be considered special hazardous waste.
Empty cans, even if completely emptied, must not be dispersed in the environment.
The aerosol container overheated to a temperature above 50 ° C may burst even if it contains a small residue of gas.
Disposal must take place in an authorized place and in compliance with the laws in force.
The transport of waste may be subject to ADR.
European waste catalog code (contaminated containers):
Aerosol as domestic waste is excluded from the application of the aforementioned rule.
The exhausted aerosol for professional / industrial use can be classified:
15.01.11 *: metallic packaging containing dangerous solid porous matrices, including empty pressure containers.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: UN 1950

14.2. UN proper shipping name

ADR / RID: AEROSOLS
IMDG: AEROSOLS
IATA: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es)

ADR / RID: Class: 2 Label: 2.1

IMDG: Class: 2 Label: 2.1

IATA: Class: 2 Label: 2.1



14.4. Packing group

ADR / RID, IMDG, IATA: -

SECTION 14. Transport information ... / >>

14.5. Environmental hazards

ADR / RID: NO
IMDG: not marine pollutant
IATA: NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: --	Limited Quantities: 1 lt	Tunnel restriction code: (D)
	Special provision: 190, 327, 344, 625		
IMDG:	EMS: F-D, S-U	Limited Quantities: 1 lt	
IATA:	Cargo:	Maximum quantity: 150 kg	Packaging instructions: 203
	Passengers:	Maximum quantity: 75 kg	Packaging instructions: 203
	Special provision:	A145, A167, A802	

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P3a

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product
Point 40
Contained substance
Point 75
Point 69 Methanol
REACH Reg.: 01-2119433307-44-XXXX

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors
not applicable

Substances in Candidate List (Art. 59 REACH)
On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)
None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:
None

Substances subject to the Rotterdam Convention:
None

Substances subject to the Stockholm Convention:
None

Healthcare controls
Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

VOC (Directive 2004/42/EC) :
Special finishes - All types.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1A	Flammable gas, category 1A
Aerosol 1	Aerosol, category 1
Aerosol 3	Aerosol, category 3
Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Press. Gas	Pressurised gas
Press. Gas (Liq.)	Liquefied gas
Acute Tox. 3	Acute toxicity, category 3
STOT SE 1	Specific target organ toxicity - single exposure, category 1
Acute Tox. 4	Acute toxicity, category 4
Asp. Tox. 1	Aspiration hazard, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
STOT SE 2	Specific target organ toxicity - single exposure, category 2
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H370	Causes damage to organs.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H371	May cause damage to organs.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

LEGEND:
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration

SECTION 16. Other information ... / >>

- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)
27. Delegated Regulation (UE) 2024/2564 (XXII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:
The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.
This document must not be regarded as a guarantee on any specific product property.
The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.
Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION
Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.
Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.
Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

SECTION 16. Other information ... / >>

Changes to previous review:
The following sections were modified:
02 / 09.